

Form 3160-5

Page 2

E. C. Hill "B" #16

Tail in w/220 sx Premium 50:50 Poz w/0.6% Halad Displaced plug w/106 BFW. PD @ 12:45 AM 10-3-96. Circ 100 sx to surface. ND BOP, set slips on 5-1/2" csg. Released rig @ 5:30 AM CDT 10-3-96.

- 10-8-96 RIH w/4" select fire csg gun & perforate 3 JSPF 0.44" 19 GM charges from 5248'-5287', 5300'-5373', 5401'-5440 (120 holes). Spot 2 bbls acid across perms. PU & set pkr @ 5140'. Acidize w/6000 gals 15% NEFE HCl & 180 ball sealers. AIR 4.5 BPM, Avg press 2019 psi, 500 psi ball action. ISIP 1002 psi, 15 mins 419 psi.
- 10-9-96 Released pkr & POOH, frac perms 5248'-5440' dwn 5-1/2" csg w/25# Delta Frac & 16/30 Ottawa Sand, total 97,559 gals, 186,000# sand. ISIP 1752 psig, 15 mins 1259 psig.
- 10-10-96 PU Arrowset-1 pkr, TIH to 5143', ND BOP, packoff WH, circ well w/2% KCL w/pkr fluid. Unpack WH, Set pkr w/6K tension, repack WH. Load csg to 500 psi. RU Swab, IFL 400', FFL 1100'.

Record of Inclination attached.