## DRILLING PROGRAM

Attached to Form 3160-3

Smith & Marrs, Inc.

Wills Federal No. 15 990' FNL & 1980' FEL Unit Letter B, NW/NE Section 35, T26S, R37E Lea County, New Mexico

## 1. Geologic Name of Surface Formation: Permian

## 2. Estimated Tops of Important Geologic Markers and

3. Estimated Depths of Fresh Water, Oil, and Gas:

<u>Formation</u>	Depth	Fluid Content
Permian Anhydrite	Surface 500' 900' 1350	Fresh water at +250'
Top of Salt Base of Salt	2400'	
Queen Sand Total Depth	3920' 4000'	Oil

No other formations are expected to give up oil, gas, or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 8 5/8" casing at 1300' into the anhydrite and circulating cement to surface. 5-1/2" production casing will be set at TD.

The pore pressure gradient is normal (+8.4 ppg) down through the Queens. No abnormal pressures are anticipated.

## 4. Casing and Cementing Program

	Casi	ng		
<u>Hole Size</u>	From	To	<u>Casing OD</u>	Weight, Grade, Coupling, Cond,
12 1/4"	0'	1,300'	8-5/8"	24# J55 LTC new
7-7/8"	0	TD	5-1/2"	17# J55 LTC new

All used casing will be drifted and hydrostatically tested to at least 90% of new pipe rating.