

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO.

30-025-33717

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

20035

7. Lease Name or Unit Agreement Name

State 19

8. Well No.

1

9. Pool name or Wildcat

Wildcat (Morrow)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Cobra Oil & Gas Corporation

3. Address of Operator

P.O. Box 8206 Wichita Falls, Texas 76307-8206

4. Well Location

Unit Letter G : 1865 Feet From The North Line and 2165 Feet From The East Line

Section 19

Township 24S

Range 33E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3541 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud Well 1:30 PM 1/31/97.

Drill 26" surface hole to 655. Run 20" 94# K-55 BT & C Casing and set it 650. Halliburton cemented with 1150 sacks Premium Plus w/2% Ca Cl and 6% gel, mixed at 13.5 ppg, 1.76 cuft/sx followed by 510 sacks Premium Plus w/2% Ca Cl mixed at 14.8 ppg, 1.34 cuft/sx. Plug down at 10:15 AM 2/3/97. Used five centralizers. Test 20" casing to 500 psi for 30 minutes. Drill 17½" hole out of 20" casing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rory Edwards

TITLE

Production Supervisor

DATE

2/5/97

TYPE OR PRINT NAME

Rory Edwards

TELEPHONE NO.

(817) 716-5100

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: