Form 3160-5 (JUNE 1990)

ED STATES Ui DEPARTMENT OF THE INTERIOR N.M. Oil Cons. BUREAU OF LAND MANAGEMENT P.O 0x 1980

FORM APPROVED
Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. LC - 030181-A

DONLAG	LILLE NIA PROMI	5. Lease Designation and Serial No.
Hobbs, NM 88241 SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		LC - 030181-A
		6. If Indian, Allottee or Tribe Name
DO INC GOO THE TENT	ION FOR PERMIT-" for such proposals	
		7 MAN A Assessment Designation
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
. Type of Woll Oil Gas		8. Well Name and No.
X Well Well Other		H.G. Moberly "A" Fed. #3
2. Name of Operator ARMSTRONG ENERGY CORPORATION		9. API Well No.
3. Address and Telephone No. P.O. Box 1973 Roswell, New Mexico 88202-1973 505-623-8726		30-0
		10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey		Rhodes
2310' FSL & 660' FEL		11. County or Parish, State
		Lea, New Mexico
Sec. 8, T26S, R37E	THE SELECTION DES	CORT OR OTHER DATA
CHECK APPROPRIATE BO	OX(s) TO INDICATE NATURE OF NOTICE, REP	ORI, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction Non-Routine Fracturing
X Subsequent Report	Plugging Back	Water Shut-Off
	Casing Ropair Altering Casing	Conversion to Injection
Final Abandonment Notice	X OTHER Run Surface Casing	Dispose Water
	and Cement Job	(Note: Report results of multiple completion on Well completion or recompletion resport snd Log form.)
 Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and true vertical depths 	all pertinent details, and give pertinent dates, including estimated date of starting any properties and zones pertinent to this work.)**	Mobosed motic. It was a macromany miner
	and the second s	
02-04-98 Drilled 22" hole to 40'.	Set 40' of 14" casing. Ready mix to surface.	
and an an an analysis Della	11- 1036	
02-06-98 Spud 12 1/4" hole, Dril	110 1026.	
to		
02-07-98		
02-07-98 Set 8 5/8" J55 24# API	ST&C casing @ 1026'. Halliburton cemented w	with
to 390 sy I T PP cement with 5# salt plus 200 sx PP cement with 2% caci.		· · · · · · · · · · · · · · · · · · ·
02-08-98 Plug down at 12:00 p.m. midnight on 02-07-98. Circ. 45 sx to pit. Press upon plug to 800# for 12 min., release pressure and float held O.K. Witnessed by Mr. Steve Caffey, Hobbs - BLM.		ssure
		The state of the s
		The Standard Control of the Control
		acs
02-08-98 Test BOP, Blind Rame	s & Pipe Rams to 1000 psi, held O.K. Resume	drlg.
with 7 7/8" hole using	brine water.	1 To the second
14. I horoby certify that the foregoing is true and correct		Date 02-09-98
simul 7 Lok 144	Title Consultant	