State of New Mexico Ainerals and Natural Resources Department Ener,

Form C-103 Revised 1-1-89

OIL CONSERVATION DIVISION WELL API NO. DISTRICT 2040 Pacheco St. P.O. Box 1980, Hobbs, NM 88240 30-025-34148 NM 87505 Santa Fe, 5. Indicate Type of Lease DISTRICTI P.O. Drawer DD, Artesia, NM 88210 STATE FEE L 6. State Oil & Gas Lease No. DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 21606 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: State 30 WELL X OTHER WELL 8. Well Na. 2. Name of Operator Cobra Oil & Gas Corporation 9. Pool name or Wildcat Address of Operator Wildcat - Bone Springs P.O. Box 8206 Wichita Falls, Texas 76307-8206 Well Location 1980 Line Feet From The North Line and 660 Feet From The Unit Letter -County **NMPM** 24S Range Township Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3546 gr Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: ALTERING CASING REMEDIAL WORK PLUG AND ABANDON PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. CHANGE PLANS TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER:. OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1/15/99 Spot 25 sx Class H cement plug mixed @ 15.6 ppg, yield 1.18 cu ft/sx from 10,200'-10,077'. 1/18/99 Tag TOC @ 10,311'. Notified NMOCD, Gary Wink, to get approval to set CIBP @ 10,200'. Dump 35' cement on top. TOC @ 10,165'. 1/19/99 Stretch casing, showed to be free @ 8000'. Notified NMOCD, Gary Wink. Plug @ 9550' not required if casing cut @ 8000'. 1/20/99 Cut casing @ 8000'. Began pulling casing. 1/21-1/23/99 Continued pulling casing. Spotted 75 sack Class C cement plug mixed @ 14.8 ppg, yield 1.32 cu ft/sx 1/24/99 Tag TOC @ 7942'. Spot 50 sx cement plug mixed @ 14.8 ppg @ 5050'. WOC 4 hrs. Tagged TOC @ 4927'. Spotted 50 sack plug, Class C cement mixed @ 14.8 ppg, yield 1.32 cu ft/sx from 2600'-2500'. Spotted 50 sx Class C plug mixed @ 14.8 ppg, yield 1.32 cu ft/sx from 700'-600'. Spot 10 sack plug Class C cement mixed @ 14.8 ppg, yield 1.32 cu ft/sx from 20'-surface. 1/25/99 Cement @ surface in 10-3/4" casing. Capped wellhead, installed dry hole marker, backfilled cellar, cut off deadmen. Rigged down, moved off location. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Production Supervisor 940 SIGNATURE . **теценноме но.** 716-5100 Rory Edwards TYPE OR PRINT NAME (This space for State Use)