

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Geology, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-34148
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 21606
7. Lease Name or Unit Agreement Name State 30
8. Well No. 1
9. Pool name or Wildcat Wildcat - Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator Cobra Oil & Gas Corporation	
3. Address of Operator PO Box 8206, Wichita Falls, Tx 76307	
4. Well Location Unit Letter <u>B</u> : <u>660</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>30</u> Township <u>24S</u> Range <u>33E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3546' Gr	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Rig up Halliburton Coiled Tubing Unit and motor, drill cement in 2-7/8" tubing to 15,530'. Rig up Schlumberger, perf Morrow sand 15,431' - 15,437' with 25 holes, 2-1/8" PDS gun, 60° phasing. Flow test well. Run bottom hole pressure build up. Prepare to plug Morrow perfs and test Atoka sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rory Edwards TITLE Production Supervisor DATE 2-17-98
(940)
TYPE OR PRINT NAME Rory Edwards TELEPHONE NO. 716-5100

(This space for State Use) ORIGINAL SIGNED BY CHRIS WILLIAMS
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: