

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO.
30-025-34307

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
E-5898

7. Lease Name or Unit Agreement Name

Bell Lake

8. Well No.
20

9. Pool name or Wildcat
Bell Lake South (Atoka)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☐ DRY ☒ OTHER _____
b. Type of Completion:
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIRT RESVR ☐ OTHER _____

2. Name of Operator
Kaiser-Francis Oil Company

3. Address of Operator
P. O. Box 21468, Tulsa, OK 74121-1468

4. Well Location
Unit Letter G : 1650 Feet From The North Line and 1980 Feet From The East Line
Section 6 Township 24S Range 34E NMPM Lea County

10. Date Spudded 4/22/98 11. Date T.D. Reached 6/9/98 12. Date Compl. (Ready to Prod.) 7/22/98 (Dry) 13. Elevations (DF & RKB, RT, GR, etc.) 3606 GR 14. Elev. Casinghead -

15. Total Depth 13366 16. Plug Back T.D. 12960 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By Rotary Tools ☒ Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name 12522' - 12534' Atoka 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run PE-AI-AL/MCFL 22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8	48	651	17 1/2	450 sxs	-0-
9 5/8	40	5195	12 1/4	1550 sxs	-0-
7	26	12150	8 3/4	1075 sxs	-0-

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
4 1/2	11978	13366	1.75	-	2 3/8	11950	11950

26. Perforation record (interval, size, and number)
13024'-13028', 13087'-13089' (4 SPF)
12522'-12534' (2 SPF)
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
13024 - 13089 1500 g. 7 1/2% NEFE
CIBP @ 12970' w/10' cmt on top
12522 - 12534 1500 g. 15% NEFE

28. PRODUCTION
Date First Production None Production Method (Flowing, gas lift, pumping - Size and type pump) - Well Status (Prod. or Shut-in) Shut-in
Date of Test None Hours Tested - Choke Size - Prod'n For Test Period - Oil - Bbl. - Gas - MCF - Water - Bbl. - Gas - Oil Ratio -
Flow Tubing Press. - Casing Pressure - Calculated 24-Hour Rate - Oil - Bbl. - Gas - MCF - Water - Bbl. - Oil Gravity - API - (Corr.) -

29. Disposition of Gas (Sold, used for fuel, vented, etc.) None Test Witnessed By -

30. List Attachments
Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Printed Charlotte Van Valken-Tide Technical Coord-Date 4/19/00
Signature C. Jan Alkenburg inator

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico

T. Army	T. Canyon	12129	T. Ojo Alamo	I. Penn. "B"
T. Salt	T. Strawn	12482	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka		T. Picured Cliffs	T. Penn. "D"
T. Yates	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison
T. Queen	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya		T. Mancos	T. McCracken
T. San Andres	T. Simpson		T. Gallup	T. Ignacio Ozite
T. Gfiorietia	T. McKee		Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	
T. Blinebry	T. Gr. Wash		T. Morrison	
T. Tubb	T. Delaware Sand	5130	T. Todillo	
T. Drinkard	T. Bone Springs	8662	T. Entrada	
T. Abbo	T. Morrow	12983	T. Wingate	
T. Wolfcamp			T. Chinle	
T. Penn			T. Permain	
T. Cisco (Bough C)			T. Penn "A"	

No. 1, from	to	No. 3, from	to
No. 2, from	to	No. 4, from	to

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

From	To	Thickness in Feet	n/a - dry
Lithology			