

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-025-34403

Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Lease Name or Unit Agreement Name
C. T. Bates

Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

Name of Operator
Doyle Hartman

Well No.
3

Address of Operator
P. O. Box 10426, Midland, TX 79702

Pool name or Wildcat
Rhodes (Y-7R) Gas

Well Location
Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line
Section 10 Township 26S Range 37E NMPM Lea County

Elevation (Show whether DF, RKB, RT, GR, etc.)
2987' GL (3004' RKB)

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Pressure test of 5-1/2" O.D. liner top ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-30-98: Moved in and rigged up well service unit. Installed heavy-gauge 8-5/8" x 7" casing swedge and 7" x 2-3/8" x 3" 3000-psi Type MR tubinghead. Ran into hole with drill string consisting of 4-3/4" bit, (6) - 3-3/8" O.D. drill collars, and 2-3/8" O.D., 4.7 lb/ft, J-55 EUE tubing. By pipe tally, found top of 5-1/2" O.D. liner at 2135.36' RKB and top of landing collar at 3587.43' RKB. Drilled out landing collar and 5' of hard cement.

7-1-98: Drilled an additional 7' of hard cement to a depth of 3601' RKB. Rigged up kill truck-transport and circulated hole clean with 170 bbl 2% KCL water. Pressure tested tubinghead, casing, and liner top to 3000 psi. Pressure held okay. Logged well with GRN-CCL log. Loggers PBTD at 3595' RKB. Set 1' x 5-1/2" O.D. CIBP @ 3593'-3594'. New PBTD @ 3593'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Starla Russell

TITLE Production Anayst

DATE 07-01-98

TYPE OR PRINT NAME Starla Russell

TELEPHONE NO. 915-684-4011

(This space for State Use)

APPROVED BY

TITLE

DATE

JUL 10 1998

CONDITIONS OF APPROVAL, IF ANY: