CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210	OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87505				WELL API NO. 30-025-34404 sIndicate Type of Lease STATE FEE			
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410					₅State Oil & Gas Leas	se No.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)					*Lease Name or Unit Agreement Name C. T. Bates			
1Type of Well: OIL GAS WELL WELL	OTHER							
2Name of Operator Doyle Hartman					₃Well No. 4			
3Address of Operator P.O. Box 10426; Midland, TX 79702 (915) 684-4011					Pool name or Wildcat Rhodes (Y-7R) Gas			
Well Location Unit Letter N : 660	Feet From TheSouth		_ Line and	2145	Feet From The	West	Line	
Section 10	Township 26S		ange	37E	NMPM	Lea	County	
	10Elevation (Show wheth 2984' G.L. (3001' F		RKB, RT, GR, etc.)					
	ppropriate Box to Indica	le Na	ture of Notic					
NOTICE OF IN	ITENTION TO:			SUBS	SEQUENT RE			
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK					ALTERING CA		
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DRILLING O				PNS.	PLUG AND ANE	3ANDONMENT	
PULL OR ALTER CASING			CASING TEST AND CEMENT JOB					
OTHER:			OTHER:					Ш
**Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Leveled 330' x 190' drilling pad area. Surfaced pad with 1404 cu. yds. of caliche. At 660' FSL & 2145' FWL Section 10, dug 17' deep hole and installed 6'd x 17' jt of 14-gauge corrugated pipe. Moved in Abbott Brothers LDH-40 rig. At 12:30 P.M., CDT, 8/28/98, commenced drilling 24" hole. Drilled 24 " hole to 76' BGL (2' into hard layer of red clay and coarse gravel at 74' BGL). Ran and welded 3 jts (91') of 20" O.D., 94 lb/ft, H-40 slip x slip casing. Landed casing at 93' RKB (76' BGL + 17' KBC), with 14.7' of 20" casing above G.L. to serve as a riser joint. Cemented casing over open-hole section and lower 11' of corrugated cellar can with 405 cu. ft. Cut and removed uncemented upper 6' section of corrugated pipe. Installed pre-fabricated 10' x 10' x 6' steel-frame cellar box, dug emergency overflow pit, and installed 12.25" O.D. welded-steel drain line from cellar to emergency overflow pit. Work completed 9-1-98. Now ready to drill 17.5" hole to 1300' RKB.								
I hereby certify that the information above	is true and complete to the best of my		dge and belief.			DATE 09-	01-98	
TYPE OR PRINT NAME DON Mashburn	- Comment	''	<u></u>			TELEPHONE NO.)11
(This space for State Use)	CHICKEAL SIGNED BY							
(Ting space for ware easy	GARY WINK	_				•	EP 28 1	998
APPROVED BY	\$ 17.00°	1	ITLE			DATE		