

District I  
PO Box 1980, Hobbs, NM 88241-1980  
District II  
PO Drawer DD, Artesia, NM 88211-0719  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION  
PO Box 2088  
Santa Fe, NM 87504-2088

Form C-101  
Revised February 10, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies

☒ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

|                                                                                              |                                         |                                |
|----------------------------------------------------------------------------------------------|-----------------------------------------|--------------------------------|
| Operator Name and Address:<br>Enron Oil & Gas Company<br>P. O. Box 2267<br>Midland, TX 79702 |                                         | OGRID Number<br>7377           |
| Property Code<br>23693                                                                       | Property Name<br>Triste Draw "34" State | API Number<br>30 - 025 - 34502 |
|                                                                                              |                                         | Well No.<br>1                  |

7 Surface Location

| UL or lot no. | Section | Township | Range | Lot Ida | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|--------|
| H             | 34      | 24S      | 33E   |         | 1921          | North            | 730           | East           | Lea    |

8 Proposed Bottom Hole Location If Different From Surface

| UL or lot no.                             | Section | Township | Range | Lot Ida | Feet from the   | North/South line | Feet from the | East/West line | County |
|-------------------------------------------|---------|----------|-------|---------|-----------------|------------------|---------------|----------------|--------|
| Proposed Pool 1<br>Johnson Ranch Wolfcamp |         |          |       |         | Proposed Pool 2 |                  |               |                |        |

|                     |                           |                       |                      |                                  |
|---------------------|---------------------------|-----------------------|----------------------|----------------------------------|
| Work Type Code<br>N | Well Type Code<br>G       | Cable/Rotary<br>R     | Lease Type Code<br>S | Grossed Level Elevation<br>3500' |
| Multiple            | Proposed Depth<br>14,200' | Formation<br>Wolfcamp | Contractor           | Spud Date<br>10/1/98             |

21 Proposed Casing and Cement Program

| Hole Size | Casing Size         | Casing weight/foot | Setting Depth | Sacks of Cement | Estimated TOC |
|-----------|---------------------|--------------------|---------------|-----------------|---------------|
| 14 3/4"   | 11 3/4 H40 ST&C     | 42#                | 650           | 350 CL C        | Surface       |
| 11"       | 8 5/8 J55 LT&C      | 32#                | 5000          | 1050 C, Prem+   | Surface       |
| 7 7/8"    | 5 1/2 S95/P110 LT&C | 17#                | 13000         | 1180 Prem       | 4500'         |
| 4 3/4"    | 2 7/8 N-80          | 6.5#               | 14200         | 135 Prem        | 12300         |

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

11 3/4"-200 sx Prem Plus, 3% Econolite, 2% Calcium Chloride, 0.25#/sx Flocele  
150 sx Prem Plus, 2% Calcium Chloride  
8 5/8"- 800 sx Interfill C, .25#/sx Flocele  
250 sx Premium Plus, 2% Calcium Chloride  
5 1/2"- 930 sx Premium, 3% Econolite, 5#/sx Salt (3%), .25#/sx Flocele  
250 Prem 50/50 Poz mix 'A', 2% Halliburton-Gel First 2%, 0.5% Halad-322,  
0.2% HR-5.  
2 7/8"- 135 sx Premium Cement, 0.3% Halad-344, 0.3% Halad-413, 0.3% Super CBL, 0.3% SCR-100  
BOP Diagram attached

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

Title:

Date:

Linda Johnston

Agent

9/30/98

Phone:

(915) 694-8228

OIL CONSERVATION DIVISION

Approved by:

ORIGINAL SIGNED BY CHRIS WILLIAMS  
DISTRICT I SUPERVISOR

Approval Date:

NOV 02 1998

Expiration Date:

Conditions of Approval:

Attached ☐

