

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address: Enron Oil & Gas Company P. O. Box 2267 Midland, TX 79702		OGRID Number 7377
Property Code 23693	Property Name Triste Draw "34" State	API Number 30-025-34502
		Well No. 1

7 Surface Location									
UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
H	34	24S	33E		1921	North	730	East	Lea

8 Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 Johnson Ranch Wolfcamp					Proposed Pool 2				

Work Type Code N	Well Type Code G	Cable/Rotary R	Lease Type Code S	Ground Level Elevation 3500'
Multiple	Proposed Depth 14,200'	Formation Wolfcamp	Contractor	Spud Date 10/1/98

21 Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/2	13 3/8 H40A ST&C	42#	650	550 CL C	Surface
12 1/4	9 5/8 J55 LT&C	40#	5000	1000 Prem+/2500 CL C	to Surface
8 3/4	7 P110 LT&C	26#	12700	1000 CL H	4500
6 1/8	3 1/2 P105 CSHYD	9.3#	14200	500 CL H	12300

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

13 3/8: Cement to surface w/300 sx CL C 50/50 Poz + 10% gel & 8#/sx salt & 1/4#/sx flocele followed by 250 sx CL C + 2% CaCl2
9 5/8: Cement to surface w/1000 sx Prem 50/50 poz + 10% gel + 8#/sx salt + 1/4#/sx flocele and 250 sx CL C = 2% CaCl2
7": Cement w/800 sx CL H + 3% Econolight+5#/sx salt + 1/4#/sx flocele followed by 200 sx Prem 50/50 poz + 0.5% Halad-477+0.25#/sx D-air-1 + 0.17% HR-5 + 0.5#/sx CaCl. This is designed to bring TOC to 4500'±
3 1/2: 225 sx Prem+ 3/4% Halad 413- + .3% Halad 344 + 3% SER-100 TOC: 12300±
BOP Diagram attached

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

Title:

Date:

Linda Johnston

Agent

9/17/98

Phone: (915) 694-8228

OIL CONSERVATION DIVISION

Approved by:

Title:

Approval Date:

Conditions of Approval:

Attached ☐

Expiration Date: