

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all specific tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	1200.0	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	1400.0	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	2794.0	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	2954.0	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	3204.0	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____		T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____		T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____		T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____		T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____		T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____		T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____		T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____		T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____		T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____		T. _____	T. Chinle _____	T. _____
T. Penn _____		T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____		T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from 2990' to 3258' (Gas) No. 3, from to
No. 2, from to No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1200.0	1400.0	200.0	Anhydrite, Shale				
1400.0	2794.0	1394.0	Salt, Anhydrite Shale				
2794.0	2954.0	160.0	Dolomite, Anhydrite Shale				
2954.0	3204.0	250.0	Sandstone, Dolomite, Shale Anhydrite				
3204.0	3550.0	346.0	Dolomite, Sandstone, Shale				