

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO	30-025-35028
5. Indicate Type of Lease	STATE FEE ☒
6. State Oil / Gas Lease No.	
7. Lease Name or Unit Agreement Name	F.B. DAVIS
8. Well No.	8
9. Pool Name or Wildcat	TEAGUE DRINKARD/ABO NORTH

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.	
1. Type of Well:	OIL WELL ☒ GAS WELL OTHER
2. Name of Operator	TEXACO EXPLORATION & PRODUCTION INC.
3. Address of Operator	205 E. Bender, HOBBS, NM 88240
4. Well Location	Unit Letter B : 960 Feet From The NORTH Line and 2245 Feet From The WEST Line Section 8 Township 23S Range 37E NMPM LEA COUNTY
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

PLUG AND ABANDON

REMEDIAL WORK

ALTERING CASING

TEMPORARILY ABANDON

CHANGE PLANS

COMMENCE DRILLING OPERATION

PLUG AND ABANDONMENT

PULL OR ALTER CASING

CASING TEST AND CEMENT JOB

OTHER:

OTHER:

COMPLETION ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-18-00/8-08-00: MIRU KEY 7-19-00. NUBOP. MOVE IN PIPE RACKS, DC'S. TAG TOP OF CMT @ 5944. PU HLE TO 5898'. DC TOOL @ 6040'. RU STRIPR HEAD & SWIV EL. PU 2 JTS TBG. TAG CMT @ 5944'. DRILL CMT TO 6036'. TAG DV TOOL. DRILL OUT DV TOOL. TAG CMT @ 7105'. DRILL CMT TO 7262. TEST CSG TO 2000 PSI. TEST OK. RD STRIPPER HEAD. PICKLE CSG W/500 GALS HCL. CIRC W/2% KCL. SPOT 1000 GALS 15% HCL ACR PERF INTERVAL. RUN GR/CCL LOG FR 7254-5679. PERF FR 6296-6372 7-22-00. ACIDIZE PERFS FR 6296-6372 W/3500 GALS 15% HCL. TIH V/NOTCH COLLAR & 208 JTS 2 7/8" TBG TO 6500'. FRAC DRINKARD ABO FORMATION W/123600 LBS 16/30 JORDAN SAND IN 5 STGS. TIH V/NOTCH COLLAR & 208 JTS 2 7/8" TBG TO 6500. PERF @ 6296-6372. TIH W/MA, PURGE VALVE, SN @ 6471, TAC @ 6220. NDBOP. HU FLOWLINE, UNLOAD RDS. PU FILTERS, DIP TUBE, PMP, K-BARS, RDS ON 7-28-00. INSTL 320 PMPG UNIT. LENGTH STROKE 144".

8/08/00: ON 24 HR OPT. PUMPED 58 BO, 31 BW, & 222 MCF. FINAL REPORT

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Engineering Assistant

DATE 8/22/00

TYPE OR PRINT NAME

J. Denise Leake

Telephone No. 397-0405

(This space for State Use)

APPROVED

CONDITIONS OF APPROVAL IF ANY

TITLE

DATE