State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION

WELL API NO.

STRICT II Santa Fe, NM 87505				30-025-35345			
P.O. Drawer DD, Artesia, NM 88210				sIndicate Type of Lease			
DISTRICT III					STATE	FEE	
1000 Rio Brazos Rd., Aztec, NM 87410				sState Oil & Gas Lease	No.		
CUNDRY NOTICES AND	DED0.DE0.0						
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A							
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"				Lease Name or Unit Agreement Name			
(FORM C-101) FOR SUCH PROPOSALS.)				Johnson Ranch State 28 Com			
Type of Well: OIL GAS				Johnson Ranch S	late 28 Com		
OIL GAS — WELL	OTHER						
₂Name of Operator				aWell No.			
Nearburg Producing Company							
3Address of Operator 3300 North "A" Street, Bldg 2, Ste 120, Midland, TX 79705				Pool name or Wildcat			
4Well Location				Johnson Ranch, Wolfcamp			
Unit Letter A 660 Feet From The	North	Line and	660	Feet From The	East	Line	
Section 28 Township	248	Range	33E	NMPM	Lea	County	
in Elevation (Show whether DF, RKB, RT, GR, etc.) 3521' GR							
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data							

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: 12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 05-07-02 Set 7" CIBP @ 12150', run dump bailer and cap w/ 35' of cmt. TOC @ 12,115'. 05-08-02 Circulate hole w/ mud. 05-09-02 Shot 7" csg @ 9110', could not pull csg. Spot 25 sx cmt from 9160' to 9010'. 05-10-02 Cut and pull 7" csg from 8215'. 05-10-02 Spot 35 sx cmt @ 8265', WOC and tag @ 8193'. 05-13-02 Spot 40 sx cmt f/ 6139' to 6026'. 05-14-02 Spot 40 sx cmt f/ 5259', WOC & tag TOC @ 5133'. 05-14-02 Spot 40 sx cmt f/ 3650' to 3529'. 05-14-02 Spot 40 sx cmt f/ 1600' to 1479'. Approved as to plugging of the Well Bore. 05-14-02 Spot 40 sx cmt f/ 859', WOC & tag TOC @ 7". 05-14-02 Spot 60 sx cmt f/ 60' to surface. 05-15-02 Cut off wellhead and install dry hole markerbility under bond is retained until surface restoration is completed. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Regulatory Analyst SIGNATURE 915/686-8235 TYPE OR PRINT NAME Kim Stewart

(This space for State Use)

APPROVED BY

TITLE

OC FIELD REPRESENTATIVE IVSTAFF MANAGER

CONDITIONS OF APPROVAL, IF ANY: