

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-35502

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil / Gas Lease

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

b. Type of Completion:

NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐

2. Name of Operator

TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator

15 SMITH ROAD, MIDLAND, TX 79705

4. Well Location

Unit Letter B : 990' Feet From The NORTH Line and 2310' Feet From The EAST Line

Section 9 Township 23-S Range 37-E NMPM LEA COUNTY

10. Date Spudded

1/9/2002

11. Date T.D. Reached

1/25/2002

12. Date Compl. (Ready to Prod.)

3/27/2002

13. Elevations (DF & RKB, RT, GR, etc.)

3310'

14. Elev. Csghead

15. Total Depth

7250'

16. Plug Back T.D.

17. If Mult. Compl. How Many Zones?

18. Intervals

Rotary Tools

Cable Tools

Drilled By

19. Producing Interval(s), of this completion - Top, Bottom, Name

6708-7038' ABO 6304-6616 DRINKARD, 6105-6264' TUB

20. Was Directional Survey Made

YES

21. Type Electric and Other Logs Run

GR/CCL, GRSL, PECFL

22. Was Well Cored

NO

CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8 5/8"	24#	1205'	12 1/4"	700	
5 1/2"	17#	7250'	7 7/8"	2800	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	7110'	

25. TUBING RECORD

26. Perforation record (interval, size, and number)

6804-13, 6816-39, 6850-54, 6876-81, 6886-97, 6900-04, 6912-32, 6934-40, 6946-57, 6960-68, 6972-88, 6994-7002, 7006-12, 7022-29, 7032-38, 6708-11, 6723-31, 6740-49, 6304-34, 6352-56, 6382-84, 6387-92, 6394-97, 6448-52, 6462-74, 6488-94, 6506-09, 6514-36, 6542-20, 6552-57, 6567-77, 6580-87, 6603-16, 6605-10, 6612-21, 6630-34, 6645-56, 6677-35, 6240-46, 6264-62SS

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED

6708-7038' 15,000 GALS 20% NEFE, 12,000 GALS WF

6304-6616 13,450 GALS 20%, 7500 GALS WF125

6105-6264' FRAC (SPOT ACID)

28. PRODUCTION

Date First Production

4/24/2002

Production Method (Flowing, gas lift, pumping - size and type pump)

PUMPING 2 1/2"X1 3/4"X20'

Well Status (Prod. or Shut-in)

PROD

Date of Test

5-08-02

Hours tested

24 HRS

Choke Size

Prod'n For Test Period

Oil - Bbl.

48

Gas - MCF

668

Water - Bbl.

52

Gas - Oil Ratio

Flow Tubing Press.

Casing Pressure

Calculated 24-Hour Rate

Oil - Bbl.

Gas - MCF

Water - Bbl.

Oil Gravity - API -(Corr.)

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

SOLD

Test Witnessed By

30. List Attachments NOTARIZED DEVIATIONS

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Regulatory Specialist

DATE

6/13/2002

TYPE OR PRINT NAME

J. Denise Leake

Telephone No.

915-687-7375

H.W. Jones "J"

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy		T. Canyon	T. Ojo Alamo		T. Penn "B"
T. Salt	1137	T. Strawn	T. Kirtland-Fruitland		T. Penn "C"
B. Salt		T. Atoka	T. Pictured Cliffs		T. Penn "D"
T. Yates	2845	T. Miss	T. Cliff House		T. Leadville
T. 7 Rivers		T. Devonian	T. Menefee		T. Madison
T. Queen		T. Silurian	T. Point Lookout		T. Elbert
T. Grayburg	3666	T. Montoya	T. Mancos		T. McCracken
T. San Andres	3836	T. Simpson	T. Gallup		T. Ignacio Otzle
T. Glorieta	5064	T. McKee	T. Base Greenhorn		T. Granite
T. Paddock	5250	T. Ellenburger	T. Dakota		T.
T. Blinberry	5566	T. Gr. Wash	T. Morrison		T.
T. Tubb	6094	T. Delaware Sand	T. Todilto		T.
T. Drinkard	6288	T. Bone Springs	T. Entrada		T.
T. Abo	6612	T.	T. Wingate		T.
T. Wolfcamp	7210	T.	T. Chinle		T.
T. Penn		T.	T. Permian		T.
T. Cisco (Bough C)		T.	T. Penn "A"		T.

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 3, from	to
No. 2, from	to	No. 4, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1137	2845		ANHYDRITE, DOLOMITE				
2845	3486		LIMESTONE, DOLOSTONE				
3486	3666		SANDSTONE				
3666	3836		DOLOMITE, LIMESTONE				
3836	5064		DOLOSTONE				
5064	5250		DOLOSTONE				
5250	5566		DOLOSTONE				
5566	6094		DOLOSTONE				
6094	6288		SANDSTONE, DOLOSTONE				
6288	6612		DOLOSTONE				
6612	7210		DOLOSTONE				
7210	TD		DOLOSTONE				