

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.O. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Injector

2. Name of Operator

Texaco E&P, Inc.

3. Address and Telephone No.

P. O. Box 3109 - Midland, TX 79702 915/688-4816

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter G 1980' FNL, 1980' FEL Sec. 15 T-255 R-32E

5. Lease Designation and Serial No.

LC-062300

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Unit G

8. Well Name and No.

Cotton Draw Unit #17

9. API Well No.

30-025-08188

10. Field and Pool, or Exploratory Area

Paduca Delaware

11. County or Parish, State

Lea

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Notify BLM prior to plugging and abandonment of well.
2. RUWL & set CICR @ 4650'. Sqz 65 sx below retainer & cap w/20 sx.
3. Circ. well w/25# per bbl. salt gel mud.
4. POOH to 4385'. Spot 25 sxs cmt f/4385'-4285' (base of salt).
5. POOH Perf. & sqz. @ 1206' w/pkr @ 1100'. Sqz. w/85 sx cmt. WOC & tag (top of salt 1156').
6. POOH to 818'. Spot 25 sx cmt f/818'-718' (Russler 768').
7. POOH to 450'. Perf. & 450' & circ. cmt to surface w/CICR or pkr @ 300', cmt w/125 sxs.
8. POOH to 100'. Spot 25 sx cmt plug f/100'-surface.
9. Nipple down BOP cut off wellhead & install dry hole marker. Clean location & move off.

RECEIVED
MAY 18 10 55 AM '95
OIL
AREA

14. I hereby certify that the foregoing is true and correct

Signed RJ Ward

Title Operations Engineer

Date 5/16/95

(This space for Federal or State office use)

Approved by CNA Signed by Adnan Salamah
Conditions of approval, if any:

Title Petroleum Engineer

Date 7/7/95

- SEE ATTACHED -

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

RECEIVED

JUL 11 1995
U.S. HOUSE
OFFICE

BUREAU OF LAND MANAGEMENT
CARLSBAD RESOURCE AREA

Permanent Abandonment of Wells on Federal Lands

Conditions of Approval

1. **Approval:** Plugging operations shall commence within 90 days from the approval date of plugging procedure.
2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Eddy County call (505)887-6544 ; for wells in Lea County call (505) 393-3612.
3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,696 feet; a 3M system for a well not deeper than 13,636 feet ; and a 5M system for a well not deeper than 22,727 feet.
4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" , for up to 7,500 feet of depth, mixed at 14.8 lbs./gal. with 6.3 gallons of fresh water per sack or class "H" , for deeper than 7,500 feet plugs, mixed at 16.4 lbs./gal. with 4.3 gallons of fresh water per sack.
6. **Dry Hole Marker:** All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 16-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer; such as notes and bounds).
7. **Subsequent Plugging Reporting:** Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

Following the submittal and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.

RECEIVED
JUL 11 1980
UCD HOBBS
OFFICE