

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NM-L-C06300

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Devon Energy Production Company, L.P.

3. Address and Telephone No.

20 North Broadway, Suite 1500, Oklahoma City, Oklahoma 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 2310' FEL. Unit J, Section 15, Township 25S, Range 32E, Lea County New Mexico

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

GE Jordan NCT 1 # 10

9. API Well No.

30-025-08184

10. Field and Pool, or Exploratory Area

Paduca (Delaware)

11. County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug # 1 1/31/01 Set CIBP @ 4650'

1/31/01 Circulate well with mud laden fluid

Plug # 2 1/31/01 Spot 10 sks of C cement @ 4650'

Plug # 3 1/31/01 Spot 25 sks of C cement @ 2720'. WOC & Tag @ 2234'

Plug # 4 2/01/01 Spot 25 sks of C cement @ 1180'. WOC & Tag @ 807'

Plug # 5 2/01/01 Found hole @ 750'. Circulate 215 sks of C cement down 4 1/2 up annulus to surface

2/10/01 Cut off wellhead & anchors 3' BGL. Install dry hole marker

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Candace R. Graham

Candace R. Graham

Title Engineering Technician

Date March 14, 2001

(This space for Federal or State office use)

Approved by (ORIG. SGD.) LES BABYAK

Title _____

Date 3/26/01

Conditions of approval, if any:

GW

RECEIVED

MAR 20 2001

BLM
ROSVELL, NM