

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

~~NEW OIL & GAS COMMISSION~~
~~Drawer DD~~
~~Artesia, NM~~ 88210

Approved.
Agent's No. 42-R1424

~~NEW OIL & GAS COMMISSION~~
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Water Injection
2. NAME OF OPERATOR Well
Texaco Inc.
3. ADDRESS OF OPERATOR
P.O. Box 728, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL: (Unit Letter 'E')
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC-062300
6. IF INDIAN, ALLOTTEE OR TRIBE
7. UNIT AGREEMENT NAME
Cotton Draw Unit
8. FARM OR LEASE NAME
Cotton Draw Unit
9. WELL NO.
12
10. FIELD OR WILDCAT NAME
Paduca Delaware
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 15, T-25-S, R-32-E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3448' (DF)

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Report of: Squeeze upper

perfs. & Treat Lower perfs.

(NOTE: Report results of multiple completion of zone change on Form 9-330.)

RECEIVED
JUN 1 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up. Install BOP. Pull tubing & packer.
2. Clean out. Set RBP @ 4660' & spot 10' Sand on plug.
3. Set cement retainer @ 4537'. Cement squeeze 4 1/2" Csg. perfs. 4630' - 4634' w/150 sx. Class 'H' Cement. WOC. DOC. Tested 4 1/2" Csg. to 1500# for 30 minutes, 2:30 - 3:00 PM, 5-17-82. Tested OK.
4. Clean out & pull RBP. Clean out to 4730' (PBTD).
5. Set pkr. @ 4650'. Acidize perfs 4671' - 4720' w/1000 15% NEFE Acid containing 50 gals. Pentafox in 2-equal stages. Flushed w/18 Bbls. Water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Asst. Dist. Mgr. DATE 5-27-82

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

JUL 14 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

JUL 15 1982

G.C.D.
HOBBS OFFICE