Form 9–331	Form Approved. Budget Bureau No. 42-R1424
H	1 ····································
UNITED STATESP. C. C.	Budget Bureau No. 42-R1424   Diago 5. LEASE
DEPARTMENT OF THE INTERIOF	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS O	N WELLS 7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug reservoir. Use Form 9-331-C for such proposals.)	B. FARM OR LEASE NAME
1. oil gas under gas well det other	<u>Cotton Draw Unit</u> 9. WELL NO.
2. NAME OF OPERATOR	43
TEXACO, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Paduca Delaware
. O. Box 728, Hobbs, New Mexico	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY	
below.)	<u>Sec. 20, T-25-S, R-32-E</u>
AT SURFACE:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: 330' FEL & 3	
AT TOTAL DEPTH: (Unit Lette:	r 'P') 14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATUR	RE OF NOTICE,
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	3369' (GR)
REQUEST FOR APPROVAL TO: SUBSEQUENT F	REPORT OF:
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9-330.)
	change on Form 9-330.)
(other) CONVERT TO WATER INJECTIO	ON
including estimated date of starting any proposed y	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed of measured and true vertical depths for all markers ar	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and
including estimated date of starting any proposed y	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and
including estimated date of starting any proposed measured and true vertical depths for all markers ar	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)*
including estimated date of starting any proposed we measured and true vertical depths for all markers ar Rig up. Pull rods and pump.	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 45! Set pkr. @ 4555'. Acidize per:	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gal 15% NEFE Ac
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 455	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 45! Set pkr. @ 4555'. Acidize per:	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set 0 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. 2 Clean out Drill out CIBP @ 455 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
<pre>including estimated date of starting any proposed of measured and true vertical depths for all markers and Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water.</pre>	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 45! Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and and zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. Clean out Drill out CIBP @ 455 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'. n. Set @ Ft.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. Clean out Drill out CIBP @ 455 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true and correct	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'. n. Set @Ft.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. I Clean out Drill out CIBP @ 45! Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true and correct	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'. n. Set @Ft.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. Clean out Drill out CIBP @ 455 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true and correct signed TITLE Dis	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'. n. Set @Ft. <u>Set @Ft.</u> <u>Set @Ft.</u>
including estimated date of starting any proposed of measured and true vertical depths for all markers are Rig up. Pull rods and pump. Clean out Drill out CIBP @ 45! Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection to Convert well to water injection to Subsurface Safety Valve: Manu. and Type	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. Clean out Drill out CIBP @ 459 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true and correct IGNED	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'. n. Set @Ft. <u>Set @Ft.</u> <u>Set @Ft.</u>
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. Clean out Drill out CIBP @ 455 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. : Clean out Drill out CIBP @ 45! Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.
including estimated date of starting any proposed of measured and true vertical depths for all markers ar Rig up. Pull rods and pump. Clean out Drill out CIBP @ 455 Set pkr. @ 4555'. Acidize per: Run plastic coated injection to Load Annulus W/inhibited water. Convert well to water injection Subsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true and correct SIGNED	NS (Clearly state all pertinent details, and give pertinent dates, work. If well is directionally drilled, give subsurface locations and nd zones pertinent to this work.)* Install BOP. Pull tubing. 56'. fs 4606'-4646' W/1000 gaI 15% NEFE Ac ubing W/pkr and set @ 4555'.

FEB - 6 1985 HOBER OFFICE **ب** \* And All Angels and Ange Angels and Ang

ъ.,

REGEIVED