E. W. STANDLEY DISTRICT ENGINEER DEPAR	AP	dget Bureau No. 43-B368.4. proval expires 12-31-60. Las Cruces D61369 D DEC 2 1960 LS COMON ALE MENICO
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZ SUBSEQUENT REPORT OF ALTERING CASING L	AIR
2010-0000 12, 33-00-001 139A	ECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) $ \begin{array}{c}                                     $	

#### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

### See attached program and plate.

# ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company	by
Address	
Hobbs, New Hex100	By Clerkang L. N. Long
······································	Title District Production Superintendent

#### TENNESSEE GAS AND OIL COMPANY PROGNOSIS TO DRILL AND COMPLETE

Lease: Eugene H. Perry-USA

Wall No.: 2

District: Hobbs

Field: Paduca Area

Location: 660' FWL & 660' FNL, Sec. 21, T-25-S, R-32-E, Lea Co., Now Mexico

Projected Horison: Delaware Sand

Estimated TD: 4800\*

#### Estimated Elevation: 3430' O.L.

#### Drilling, Casing, and Cement:

- 1. Drill 12 1/4" hole to approximately 350'.
- Cement 8 5/8<sup>m</sup> casing at approximately 350' w/sufficient volume to circulate.
- 3. WOC 24 hrs. Release pressure and install BOP after 12 hrs. Pressure test casing w/600 psi for 30 minutes after WOC 18 hrs.
- 4. Drill 7 7/8" hole to Delaware Sand core point at approximately 4650". Exact coring depth to be determined by wellsite Exploitation Engineer.
- 5. Core from 4650' to 4800' w/7 13/16" diamond bit.
- 6. Set 52" casing at TD w/130 sacks of 50/50 Posmix "S" and regular with 2% gel (or equivalent).
- 7. WOC 18 hrs. Run temperature survey after WOC 8 hrs. Pressure can be released if float holds; otherwise, hold pressure on casing for 8 hours.
- 8. Run tubing and pressure test casing w/1500 psig for 30 minutes after WOC 18 hrs.
- 9. Displace water w/oil.
- 10. Release rotary rig.

#### Drilling Hude

- 1. Drill w/fresh water native mud to TD. Mud properties will be adjusted to neet requirements for good samples, coring, and drill stem tests. Prior to coring or running a drill stem test, the mud should have the following properties: Viscosity 35-40, water loss 5 to 10cc or less in 30 minutes, filter cake 2/32" or less.
- 2. No oil will be added without consent of wellsite Exploitation Engineer.

#### Drill Sten Tests:

1. One drill stem test may be run in the Delaware Sand between 4600' and 4700'.

#### Drilling Time:

- 1. Record 1' drilling time from surface to TD using Geolograph.
- 2. Record 1' drilling time in addition to Geolograph while coring.

#### Drill Pipe Measurement:

- 1. Tally drill pipe on last two trips prior to reaching casing point.
- 2. Tally drill pipe in strain under company supervision at all casing points, coring points, drill stem test points, and at TD.

\_\_\_\_\_ - 189

- Alexandrian and a second and the second 

 $\label{eq:constraint} \begin{array}{l} c_{1} & c_{2} & c_{3} \\ c_{2} & c_{3} & c_{3} & c_{3} \\ c_{3} c_{3} \\ c$ 

- - - en an Na Star (Star (St
      - ,

- •

.

анан аларын алары алары алары. Аларынан алары а

المينيين ال المينيين الم المينيين الم

#### Samples:

- 1. Catch one set of 10' drilling samples from 1300' to TD unless otherwise directed by wellsite Exploitation Engineer.
- 2. No time lag will be made in catching samples and 15 minute circulating samples will be caught for a period of one hour while circulating unless otherwise directed by the wellsite Exploitation Engineer.
- 3. Samples will be washed thoroughly, sacked, and labeled as directed by the wellsite Exploitation Engineer.
- 4. Two one-quart samples will be caught and labeled of any fluid recovered by drill stem tests.

#### Hole Deviation:

- 1. Run hole deviation every 100' on surface hole.
- 2. Run hole deviation survey on each trip for bit or every 500', whichever occurs somer.
- 3. Maximum hole deviation from surface to TD shall be  $\mu^{\circ}$ .
- 4. If hole deviation changes more than 1 1/2 degrees in any 100' interval, a string reamer will be run to wipe out dog leg.
- 5. If hole deviation changes more than 2 degrees in any 100' interval, the hole shall be plugged back and straightened out.

#### SUPPEYS

- 1. Run GR/Sonie log from casing to TD and Laterolog from approximately 1400' to TD.
- 2. Run temperature survey on 5 1/2" casing string after MOC 8 hours.
- 3. Run GR correlation log through pay section after comenting 5 1/2" casing.

#### Completion:

To be determined at total depth.

ORIGINAL SIGNED BY:

APPROVED:

APPROVED

C. W. Nance

ORIGINAL SIGNED BY A. W. LANG

A. W. Lang

CWN/nl

#### 13274 (3727) 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 - 1920 -

- en en el servicio en la sectión de la se - Andrewski - Andrewski stationer and the second of Antrewski -
- 12 មករដ្ឋស្ថាន ដែលស្ថាន ស្រុះស្រុះសំខាន់សំខាន់ សម្តេចស្រុះស្រុះសំខាន់ សេសក្រាន សំខាន់សំខាន់ ដែលនៅក្នុងសំខាន់ សំខាន កាលសម្តេចសំខាន់ សំខាន់សំខាន់ សំខាន់ សំខាន់សំខាន់ សេទន៍ សំខាន់ សំពីសំខាន់ សេសក្តីសំខាន់ សំខាន់ សំខាន់ សំខាន់ សំខា សំខាន់ក្នុងសំខាន់សំខាន់សំខាន់សំខាន់សំខាន់សំខាន់ស្រុះសំខាន់សំខាន់ ស្រុះសំខាន់ សំខាន់សំខាន់ សំខាន់សំខាន់ សំខាន់ ស
  - , É . Maadata moodud aan oo oo ah 🖾 🖬 🙀
- and the second second in the second of the second second second second second second second second second second

## 

- o a been abeen abeen of the analysis of the abeen and a second and a second and a second and a second a second a The been been at an and and an abeen the second a .
- ്ന് <sup>നിന്</sup>ചിന്ത് പ്രതിക്കായം നിന്നും മംഗ്രീക്കും നിന്നും കാക്രമായിന്നും പ്രതിക്കും നിന്നും പ്രതിക്കായിന് പ്രതിക നെം. നിന്ന നായം, നിന്ന് പ്രതിക്കായം നിലക്കായം പ്രതിക്കായം പ്രതിക്കായിന്റെ പ്രതിക്കായിന് പ്രതിക്കായിന് പ്രതിക്കാ
- . I see the ender of any of Liter states datase and a contract of the second back of the back of the second of the secon
- . Tes berra glacca ara doar bertang al alina elo

#### an Sar An an an

- of a contract of source bis water and the contract states and the source of 279 0
  - A second for the particle statistical statistical field for the permanent of the second se
  - \_ <sup>2</sup>
    - 1 3 to 18 2

#### and the second second

# A FRANCE MARKO

SIGNO BY A W LAND 1020-030 

• • • • •		- 11		RVATION (		FORM C-128 Revised 5/1/57
	WEL	L LOCATION	AND ACR	EAGE DED	ICATION PLAT	•
	SEE	INSTRUCTIONS FOR			N THE REVERSE SIDE	
Operator		1977 - March Brands, and an and an and a state	SECTI	OH A		
•	ssee Gas &	Trans. Co.	Léase		Bomme	Vell No.
Unit Letter	Section	Township	Ran	Re Re Die	Perry - USA County	2
D	21	25 South		32 East	Lea Co	ounty
Actual Footage I 660	feet from the	North lin	e and 61	(n /	1.1	
Ground Level Eli		Formation	Pool	50 lee	t from the West	line Dedicated Acreage:
3406.6					<b>4</b>	Acres
who has the r another. (65 2. If the answer wise? YES	right to drill into a -3-29 (e) NMSA to question one i NO	and to produce from an 1935 Comp.) s ''no,'' have the inte If answer is ''yes,''	iy pool and to i rests of all the Type of Conso	owners been c lidation	production either for bis onsolidated by communi	. ("Ouner" means the person mself or for himself and tization agreement of other-
Owner	to question two i	• "no," list all the or	vners and their			
				Land Descrip	tion	RECEIVED
						DEC 2 1960
		SECTION B				CERTIFICATION
-660					in SECTI plere to t belief. Name Position Doctor Date Union Date Union Date Union Date	certify that the information ION A above is true and com- the best of my knowledge and
<b></b>	EGIE		2000 1500	2 1000 5	Bupervisio and correc and belief Dat	os, and that the same is true of to the best of my knowledge

\*

-