Form Approved. Budget Bureau No. 42-R1424

UNITED 5	HAIK	<b>9</b> 265,	100
DEPARTMENT OF	THE	INTER	ЮF
0501001041	CHE	WEV	

୍ୟା	LEASE	062	56%		
	LC-	005	247	 	 
_				 	 

DEPARTMENT OF THE INTERIOR	LC-0 <del>0524</del> 7
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME  Cotton Draw Unit  8. FARM OR LEASE NAME
1. oil	Cotton Draw Unit  9. WELL NO. 50  10. FIELD OR WILDCAT NAME Paduca Delaware  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T-25-S, R=32-E  12. COUNTY OR PARISH 13. STATE
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3392' (DF)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner  1. Rig up. Install BOP.  2. Test CIBP @ 4550'. Cap with 40' cement  3. Set cement retainer @ 300' circulate cer 200 sx class H Cement through hole in ca 4. Close bradenhead vlv. Squeeze approx.  5. Spot 40' cement on top of cement retaine 6. Spot 10 sx cement plug @ surface. 7. Install dry-hole marker. Clean location	ment down $4\frac{1}{2}$ " csg. using approx. sg. @ 480'. 200 sx. class H Cement. er from 260' to 300'.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	Mgr. Date 1-19-85

(This space for Federal or State office use) TITLE \_

FEB 18 1985