


NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico



MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission

	Indicate Nature of Notice by Checkin	ng Below
otice of Intention Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper
otice of Intention Pluo Well	Notice of Intention to Plug Back	Notice of Intention to Set Liner
otice of Intention SQUEEZE	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)
otice of Intention OGUN Perforate	Notice of Intention (Other)	Notice of Intention (Other)
IL CONSERVATION COMMISSION ANTA FE, NEW MEXICO	DN Hebbs , New 1 (Place)	December 28, 1953
Following is a Notice of Intention		State Bradley Lease
Fulleries Gil (Company or O)	Company	Well No (Unit)
	, T235, R32E,NI	MPM.,
We propose to plu	g above well as fellows:-Insta	Il selid cement plug
from 4865' to 495 all BST zones. W	g above well as fellems:-Insta 3' (TB). Will use estimated 5 ill spet 10 sax cement at bett et 10 sax cement at surface as	0 sax coment to cover see of 8-5/8" casing
free 4865' to 495 all BST zeacs. We at 690'. Will speaker. pproved DEO 20 195 except as follows:	3' (TB). Will use estimated 5 ill spet 10 sax cement at bett et 10 sax cement at surface as By	ion of 8-5/8° casing and install 4°x4° ground Len Oil Company Company or Operator Div. Superintendent
free 4865' to 495 all BST zeacs. We at 690'. Will speaker. pproved DEO 20 195 except as follows:	3' (TB). Will use estimated 5 ill spet 10 sax cement at bett et 10 sax cement at surface as By	is ax cement to cover the of 8-5/8° casing the install 4°x4° ground Les Oil Company Company or Operator Six. Superintendent Send Communications regarding well to:
frem 4865' to 495 all BST zenes. W at 690'. Will sp marker. DEC 00 195	3' (TB). Will use estimated 5 ill spet 10 sax cement at bett et 10 sax cement at surface as By	ion of 8-5/8° casing and install 4°x4° ground Len Oil Company Company or Operator Div. Superintendent

Address.......Bex 2227, Hebbs, New Hexica