Budget	Bureau	No.	42-R358.4
Form A	pproved	l_	

(SUBMIT IN TRIPLICATE)

•
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office				
Lease No.	LC	062087		
Unit				

NR 50 M 6 47

SUNDRY NOTICES	AND	REPORTS	ON	WILLS
----------------	-----	---------	----	-------

NOTICE OF INTENTION TO BE DRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
---	--

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER

			<i>k</i>	pril 12,	, 19
Well No. 1-19 is located	66 0 ft. fr	om $\begin{Bmatrix} \mathbf{K} \\ \mathbf{S} \end{Bmatrix}$ line a		$\operatorname{rom}\left\{egin{array}{c} \mathbf{E} \ \mathbf{W} \end{array} ight\}$ line of	sec. 19
	25-6	34-K	N.M.P.M.		
8/2 of 82/4 Sec. 19 (½ Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	New Mexico	
	Lea				
Wildcat (Field)	(Cou	nty or Subdivision)		(State or Territory)	

The elevation of the derrick floor above sea level is 3338.2 ft.

Form 9-331 a (Feb. 1951)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Operator set 409' of 7", 23# surface csg., cemented w/150 sxs (100 sxs 6% gel, 50 sxs 2% gel & 2% HA-6), drilled to 5380'. Operator requests approval to set a 10 sack plug from surface to 30°; 100° plug from 400-500°; 100° plug from 1080-1160'; 100' plug from 5100-5200', fill hole with mud between plugs, level pits, errect a marker on 7" casing, restore location to its natural contour and abandon location.

I understand	that this plan of work must receive approval in writing by	the Geological Survey before operations may be commenced.
	Ashmun & Hilliard, No. 5 Ltd.	
	303 N. Marienfeld St.	
	Midland, Texas	By Blekmen
	,	Tiple Partner