

DUPLICATE

N.

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO STATE LAND OFFICE

SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days after completion of well. Indicate questionable data by following it with (?). Submit in duplicate.

Company Gypsy Oil Company Address Tulsa, Oklahoma.
Send correspondence to Gypsy Oil Company Address Edna, New Mexico.
Assess-Runway (State) Well No. 2 in NE 1/4 of Sec. 2, T. 22N
R. 20E, N. M. P. M., San Juan Oil Field 1st County.
If State land the oil and gas lease is No. 24027 Assignment No. 2-222
If patented land the owner is _____, Address _____
The lessee is Gypsy Oil Company, Address Tulsa, Oklahoma.
If not state or patented land, give status _____
Drilling commenced May 22, 19 35 Drilling was completed June 12, 19 35
Name of Drilling contractor Laffland Brothers, Address Tulsa, Oklahoma.
Elevation above sea level at top of casing 2024' feet.
The information given is to be kept confidential until Not Confidential, 19 _____

OIL SANDS OR ZONES

No. 1, from 2425' to 2435' No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	Purpose
12"	40	8	SS	241'	None				Protect Surface water.
9-5/8"	24	8	SS	1200'	Halliburton				"
7-1/2"	24	12	SS	2500'	Halliburton				Oil string.
5"	4.7	12	SS	2400'	None				Flow string.

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12"	241'	235	Halliburton		
9-5/8"	1200'	375	Halliburton		
7" CB	2500'	400	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATED	DEPTH SHOT	DEPTH CLEANED OUT

TOOLS USED

Rotary tools were used from 0 feet to 2400' feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing July 2nd, 19 35
The production of the first 24 hours was 100 barrels of fluid of which 100 % was oil; 20 % emulsion; 20 % water; and 20 % sediment. Gravity, Be. 34.5
If gas well, cu. ft. per 24 hours 1,000,000 Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. 9000'

EMPLOYES

J.H. Moore Driller J.O. Robinson Driller
John Fildon Driller L.L. Reynolds Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3rd day of July, 19 35 Name C.P. Cummings
C.P. Cummings Position District Superintendent
Notary Public. Representing Gypsy Oil Company
My commission expires June 23-1938 Company or Operator. Edna, New Mexico.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	104		Caliche & Sand.
104	277		Water Sand & Blue Shale.
277	300		Blue Shale and Red rock.
300	720'		Shale & Shells.
710'	760		Red Red.
760	891		Shells, Shale & Red Red.
891	1076		Shale & Shells.
1076	1176		Shale, Shells & Red Red.
1176	1230		Red Shale.
1230	1340		Anhydrite.
1340	1355'		Salt.
1355'	1370'		Anhydrite & Salt.
1370	1470		Salt.
1470	1545		Anhydrite.
1545	1645		Salt, Anhydrite & Shells.
1645	1755		Salt & Anhydrite.
1755	1800		Shells Anhydrite and salt.
1800	2000		Salt & Anhydrite.
2000	2090		Anhydrite.
2090	2120		Potash & Anhydrite.
2120	2255'		Salt.
2255	2300		Anhydrite.
2300	2310		Salt.
2310	2355		Anhydrite.
2355	2365		Salt.
2365	2380		Anhydrite.
2380	2385		Salt.
2385	2417		Anhydrite.
2417	2400		Salt & Anhydrite.
2400	2701		Anhydrite.
2701	2740		Salt.
2740	2750		Anhydrite.
2750	2770		Salt.
2770	2780		Anhydrite.
2780	2810		Salt.
2810	2820		Anhydrite.
2820	2870		Salt.
2870	3000		Anhydrite.
3000	3110		Anhydrite.
3110	3120		Lime.
3120	3140		Anhydrite.
3140	3161		Lime.
3161	3167'		Brown Lime.
3167	3210		Lime.
3210	3227		Brown Lime.
3227	3400'		Lime (Total Depth).