NL., MEXICO OIL CONSERVATION COM. ISSION Santa Fe, New Mexico

banta 1 c, New Micare

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Checking Bo	elow
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON Put well (Other) on Pump
	November 22, 195	7 Jal, New Mexico
	done and the results obtained under the heading	
Three States Natural G (Company or Ope	as Company E	. J. Wells.
	, Well No. 1-L	
25-S, R 36-E, NMPM.,	Jalmat Pool,	Loa Co
The Dates of this work were as follows:	10-7-57 to 10-10-57	
nd approval of the proposed plan (was)	(Cost) obtained.	
10-7-57 - Pulled and 2777.80' of 2" EUE Tub 10-8-57 - Ran 114 - 3/ Pony rods. 10-9-57 - Assembled an	ED ACCOUNT OF WORK DONE AND RESUran tubing, installed regular muing. Removed $5\frac{1}{2}$ 8 Rd. Thd. Ord. 4" X 25' Axelson # 60 Rods, 2 - d installed Cabot B 9 - 57D Pump p gas to pumping engine and put	d anchor and seating nipple it Master Valve. 3/4" X 4" and 2 - 3/4" X 6" ing Unit and 346 F. M. Engine
10-7-57 - Pulled and 2777.80° of 2" EUE Tub 10-8-57 - Ran 114 - 3/ Pony rods. 10-9-57 - Assembled an 10-10-57 - Connected u	ran tubing, installed regular muing. Removed $5\frac{1}{2}$ 8 Rd. Thd. Orb. 4" X 25' Axelson # 60 Rods, 2 - d installed Cabot B 9 - 57D Pump	d anchor and seating nipple it Master Valve. 3/4" X 4" and 2 - 3/4" X 6" ing Unit and 346 F. M. Engine
10-7-57 - Pulled and 2777.80° of 2" EUE Tub 10-8-57 - Ran 114 - 3/ Pony rods. 10-9-57 - Assembled an 10-10-57 - Connected u	ED ACCOUNT OF WORK DONE AND RESUran tubing, installed regular muing. Removed 5½ 8 Rd. Thd. Orb. 4" X 25' Axelson # 60 Rods, 2 - d installed Cabot B 9 - 57D Pump p gas to pumping engine and put (Company) I hereby certify that	d anchor and seating nipple it Master Valve. 3/4" X 4" and 2 - 3/4" X 6" ing Unit and 346 F. M. Engine well to pumping. (Title)
DETAIL 10-7-57 - Pulled and 2777.80° of 2" EUE Tub 10-8-57 - Ran 114 - 3/ Pony rods. 10-9-57 - Assembled an 10-10-57 - Connected u	ran tubing, installed regular muing. Removed 5½ 8 Rd. Thd. Orb. 4" X 25' Axelson # 60 Rods, 2 - d installed Cabot B 9 - 57D Pump p gas to pumping engine and put (Company) I hereby certify the to the best of my keep to the best	d anchor and seating nipple it Master Valve. 3/4" X 4' and 2 - 3/4" X 6' ing Unit and 346 F. M. Engine well to pumping. (Title) It the information given above is true and companionly the seat of the companion
DETAIL 10-7-57 - Pulled and 2777.80° of 2" EUE Tub 10-8-57 - Ran 114 - 3/ Pony rods. 10-9-57 - Assembled an 10-10-57 - Connected u	ran tubing, installed regular muing. Removed 5½ 8 Rd. Thd. Orb. 4" X 25' Axelson # 60 Rods, 2 - d installed Cabot B 9 - 57D Pump p gas to pumping engine and put (Company) I hereby certify that to the best of my leading to t	d anchor and seating nipple it Master Valve. 3/4" X 4" and 2 - 3/4" X 6" ing Unit and 346 F. M. Engine well to pumping. (Title)