

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-025-09748

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

MARALO JALMAT YATES UNIT

8. Well No.
2

9. Pool name or Wildcat
JALMAT TANSILL YATES SEVEN RIVERS

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER ☐ WIW

2. Name of Operator
MARALO, INC.

3. Address of Operator
P. O. BOX 832, MIDLAND, TX 79702

4. Well Location

Unit Letter J : 2310 Feet From The SOUTH Line and 1650 Feet From The EAST Line

Section 12 Township 25-S Range 36-E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

REENTER & RECOMPLETE AS INJECTION WELL

09/02/96 DUG OUT CELLAR TO 10-3/4" SURFACE CASING, CUT DRY HOLE MARKER OFF. DRILLED 65' CEMENT SURFACE PLUG.

09/04/96 OPENED WELL AND DRILLED THRU MUD TO TOP OF CEMENT PLUG @ 540'. DRILLED 200' CEMENT TO 5-1/2" STUB @ 740'.

09/05/96 OPENED WELL, CIRCULATED CLEAN & RIH W/6-13/16" BOWEN LEAD SEAL CASING PATCH + 16 JTS 5-1/2" CASING AND LATCHED ONTO 5-1/2" STUB. SET SLIPS, NU WELLHEAD & LOADED 5-1/2" CASING, PRESSURED TO 300 PSI.

09/06/96 RIH W/4-3/4" BIT + 6 3-1/2" DC + TBG & DRILLED 60' CEMENT INSIDE 5-1/2" CASING TO 804'. RIH TO 2785'. DRILLED CEMENT & CIBP TO 2806'.

09/07/96 DRILLED OPEN HOLE TO 3049'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dorothea Logan TITLE REGULATORY ANALYST

DATE OCTOBER 10, 1996

TYPE OR PRINT NAME DOROTHEA LOGAN

TELEPHONE NO 915 684-7441

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MP