

COPIES RECEIVED		
DISTRIBUTION		
AFF		
U.S.		
D OFFICE		
DIATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

1-1-1979
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR NOTICES TO WELL OR TO REPORT ON WELLS TO A DIFFERENT RESERVOIR. USE APPLICATION FOR REPORT ON DIFFERENT RESERVOIR FOR SUCH PURPOSES.)

OIL WELL ☐ GAS WELL ☐ OTHER- Plugged Well

Name of Operator
Maralo, Inc. (Atlantic (Sinclair Repllo))

Address of Operator
P. O. Box 832, Midland, Texas 79702

Location of Well
UNIT LETTER 0 330 FEET FROM THE South LINE AND 2310 FEET FROM
THE East LINE, SECTION 12 TOWNSHIP 25-S RANGE 36-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
N/A

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.
N/A

7. Unit Agreement Name

8. Farm or Lease Name
Gloyd

9. Well No.
1

10. Field and Pool, or Valued
Jalmat

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ Re-PLUG AND ABANDON ☒ REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOG ☐
OTHER ☐ OTHER ☐

SUBSEQUENT REPORT OF:

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Estimated date of starting work will be January 15, 1979.

We propose to replug this well in the following manner:

Remove surface plug; remove cement plug from 970' to 1000'.

Replug as follows:

- 1 - tag cement plug at 3008'; add 50 sx cement plug; if plug is not @ 3008' - tag new plug.
- 2 - pull above cement plug - displace holw with fresh water containing 5#/bbl. gell.
- 3 - 7" shot off @ 2450'; set 50 sx plug (100') 50' in and 50' out of 7" from 2500' to 2400'.
- 4 - 10 3/4" set @ 2450'; set 50 sx plug (100') 50' in and 50' out of 10 3/4" from 2042' to 1942'.
- 5 - T/anhy - 1165'; set 50 sx plug (100') from 1150' to 1050'.
- 6 - 10 3/4" shot off @ 60'; set 100 sx plug (132') from 130' to surface.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry S. [Signature] TITLE Drilling Superintendent DATE Dec. 5, 1979

APPROVED BY [Signature] TITLE [Signature] DATE [Signature]

CONDITIONS OF APPROVAL, IF ANY