DISTRIBUTION	Supersedes Old
SANTA FE N MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE	· .
U.S.G.S.	5a. Indicate Type of Lease
LAND OFFICE	State Fee
OPERATOR	5. State Oil & Gas Lease No.
	5. State On & Gus Lease No.
	N.A.
SUNDRY NOTICES AND REPORTS ON WELLS	
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
I. OIL CAS	7. Unit Agreement Name
WELL OTHER- P & A	
2. Name of Operator	8. Farm or Leuse Name
Maralo, Inc. (Atlantic) (Sinclair Repollo)	01 1
3. Address of Operator	9. Well No.
P. O. Box 832, Midland, Texas 79702	
4. Location of Well	10, Field and Pool, or Wildcat
T 2310 South 2310	
UNIT LETTER J 2310 FEET FROM THE SOUTH LINE AND 2310 FEET FROM THE	LET FROM Jalmat
East 12 25-S 36-E	
THE East LINE, SECTION 12 TOWNSHIP 25-S RANGE 36-E	_ NMPM. (\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea
::[[[[]]]]][[][[]][][][][][][][][][][][
Check Appropriate Box To Indicate Nature of Notice, Report	or Other Data
	QUENT REPORT OF:
30032	QUENT REPORT OF
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	<u>г</u>
	ALTERING CASING ,
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	Re-Plug and abandonment
PULL OR ALTER CASING CASING TEST AND CEMENT JQB	
. OTHER	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, i	alidia animated data of access
work) SEE RULE 1103.	
1-20-80 Drld. top plug in 10 3/4" csg. Picked up total 6 - 4 3/4" December 200-80	C. Drld. and washed plug @ 490
1-22-80 Started drlg and washing to 1691' open hole.	
1-23-80 Drld & washed to 1755'. Drld. on board to 2311'	•
1-24-80 Drld & washed on wood to 2383'. Circ. hole clean.	
1-25-80 Worked 30' into top of 7" csg. OPen hole to 2580'. Washed to	o 2601'.
1-30-80 WIH $w/2$ 7/8" tbg. open ended to 2873' Spotted 50 sx 2% CaCl	. Cement plug @ 2873'.
1-31-80 Tagged cement plug @ 2684'. 189' fill. Spotted 75 sx NE cm	t. 2% CaCl2. Tagged cement
@ 2304. WOC 5 hrs. Pmpd 50 sx cmt 2% CaC12.	
2-01-80 Tagged cement plug @ 2227'. Pumped 100 sx Cl. C 2% CaCl2 @	1490'. WOC 4 hrs. Tagged cmt.
plug @ 1480'. Pmpd 75 sx Cl. C cmt. 2% CaCl2 @ 1480'.	
2-02-80 Tagged cmt. plug @ 1460'. Pmpd 75 sx cmt 2% CaC12. WOC 5 hrs	s. Tagged cmt. plug @ 1402.
Pmpd 25 sx cmt 2% CaCl2. Pld. tbg to 1165. Pmpd 50 sx cmt 2	
2 7/8" tbg. Removed BOP.	· · · · · · · · · · · · · · · · · · ·
2-03-80 Plugged top 13 3/8" csg. w/10 sx cmt.	
All pits have been filled and location has been levelled and	d cleared of junk
THE PERSON NAVO BOOM TELEFOR AND TOURISM HOW DOWN TOVETTOR AND	a executed of Julie .
	·
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Production Clerk	6-18-81
TITLE TITLE	DATE
OTT 'C OKO DIODO	TOD III ON TOO
OIL & GAS INSPEC	TOR JUN 22 1981