

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

07

1004

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

REFOLIO OIL COMPANY

W.F. Haggan

Company or Operator

Lease

Well No. 8 in 30/4 of Sec. 12 T. 25-S

R. 36-E, N. M. P. M., Jalisco, Lea County

Well is 330 feet south of the North line and 990 feet East of the East line of Section 12

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Mrs. E.C. Stephens, Address Jalisco, New Mexico

If Government land the permittee is, Address

The Lessee is, Address

Drilling commenced January 24th 1936 Drilling was completed February 22nd 1936

Name of drilling contractor Laffland Brothers, Address Tulsa, Oklahoma

Elevation above sea level at top of casing 3186 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 2, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
15 1/2	70 1/2	8	?	134'	None			
9 5/8	36 1/2	8	H'tl.	1231'	Comb. Float			
7"	24 1/2	10	"	3362'	do			
2 1/2" tbg	6.5 1/2	10	?	3384'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
19 5/8	15 1/2	144'	100	Halliburton	?	
11 1/2	9 5/8	1242'	500	"		
8 3/4	7"	3362'	500	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
Acidized with	Dewell X	1000 gal	2/20/36	3375-3387		

Results of shooting or chemical treatment 39 bbls. of oil per hour through 2 1/2" tbg.
open one round on one inch choke

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3387 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing March 1st 1936
The production of the well was 39 barrels of fluid of which 100% was oil; %
emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Joe Christensen, Driller Fred Kaskie, Driller
Gus Everett, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11th day of March 1936

Hebbs, N.M.
Place

March 11th, 1936
Date

day of March 1936

Name L. Smith

Position Dist. Supt.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION						
0	120	120	Sand & Shells						
120	152	32	Red Red						
152	225	73	" " & Shells						
225	1012	789	Shale & Shells						
1012	1100	88	Red Shale						
1100	1120	20	Anhydrite						
1120	1140	20	Shale						
1140	1204	64	Anhydrite						
1204	1254	50	Anhydrite & Salt						
1254	1345	91	Salt						
1345	1476	131	Salt, Anhydrite, Shells						
1476	1656	180	Salt & Anhydrite						
1656	1697	41	Salt, Anhydrite, Shells						
1697	1762	65	Salt & Anhydrite						
1762	1836	74	Salt						
1836	1890	54	Salt, Anhydrite, Shells						
1890	2107	217	Salt & Anhydrite						
2107	2219	112	Salt						
2219	2342	123	Salt, Anhydrite, Shells						
2342	2437	95	Salt						
2437	2551	114	Anhydrite & Salt						
2551	2571	20	Anhydrite						
2571	2656	85	Salt						
2656	2703	47	Anhydrite						
2703	2837	134	Lime						