

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

NOV 17 1947

Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 14, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Service Oil Company Lindley "B" Well No. 1 in the

Company or Operator

Lease

SE SW of Sec. 13, T. 25, R. 36, N. M. P. M.,

Cooper-Jal Field, Lea County.

The dates of this work were as follows: October 22, 1947 and November 11, 1947

Notice of intention to do the work was (was not) submitted on Form C-102 on October 20, 1947

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was plugged back from original T. D. of 3317' to 3265' by squeezing 100 sacks cement below a retainer and casing perforated from 3258' to 3250' with 24- $\frac{1}{2}$ " holes and from 3235 to 3230' with 15- $\frac{1}{2}$ " holes. Swabbing test swabbed 100% water. Was again plugged back to 3215' by squeezing below a retainer with 50 sacks cement. Casing was perforated from 3175' to 3195' with 40- $\frac{1}{2}$ " holes and swabbed 100% water. Well was then plugged back to 3165' by squeezing below a retainer with 60 sacks cement, casing perforated 3160' to 3165' with 10- $\frac{1}{2}$ " holes and 3100 to 3150' with 100- $\frac{1}{2}$ " holes and swabbed 100% water. A bridging plug was then run to 3088', casing perforated 3076' to 3085' with 27- $\frac{1}{2}$ " holes and well swabbed 100% water. With no show of oil or gas 40 sacks of cement were dumped on top of bridging plug and well left for abandonment.

Witnessed by R. W. Ely, Cities Service Oil Company, District Superintendent

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

14 th day of November, 1947

Name

Position District Superintendent

Representing Cities Service Oil Company  
Company or Operator

My commission expires March 14, 1951

Address Drawer G., Hobbs, New Mexico

Remarks:

APPROVED

NOV 17 1947

Ray G. Gubrowsky  
Name  
GAS INSPECTOR  
Title