

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

RECEIVED
NOV 17 1947
HOBBS OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

November 14, 1947

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the _____
Cities Service Oil Company **Lindley "B"** Well No. 1 in SE SW
 Company or Operator
 of Sec. 13, T. 25, R. 36, N. M. P. M., **Cooper-Jal** Field.
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

This well was originally drilled to a T. D. of 3317' in 1934 with 7" casing set at 3280' and cemented with 100 sacks and 9 5/8" casing set at 2745' and cemented with 300 sacks. Surface pipe (12 1/2") was run to 500' and cemented with 100 sacks. The well has produced until it currently makes 100% water. In an attempt to shut water off, the well was plugged back by stages to 3088' and perforating the casing with no success in shutting off water. Each perforated section was shut off by squeezing cement below a retainer set above the perforations and when there was no show of oil or gas a bridging plug was run to 3088' and 40 sacks of cement dumped on top of the plug.

It is proposed to P & A the well by reclaiming all 7" and 9 5/8" pipe that will pull, loading the hole with mud, spotting 25 sacks of cement above the salt section and cementing inside the surface pipe to the surface with 50 sacks cement leaving a marker of 4" pipe 4' above the surface.

Approved NOV 17 1947, 19____
 except as follows:

Cities Service Oil Company
 Company or Operator

By _____

Position District Superintendent

Send communications regarding well to

Name Cities Service Oil CompanyAddress Drawer C., Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By [Signature]Title OIL & GAS INSPECTOR