

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐
☐

RECEIVED

NOV 20 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
LC-032581 (A)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFL
8. FARM OR LEASE NAME
Sholes A
9. WELL NO.
5
10. FIELD OR WILDCAT NAME
Jalmat Yates Seven Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13 T-25S, R-36E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/10/80 M.I.R.U. POOH w/rods & pmp. Tag for fill at 3022'. POOH w/ tbg. WITH w/ 7" csg scraper to 3010'. POOH. WITH w/ CIBP set at 3000'. Spot 6' class cement on top CIBP. Spot 150 gals 15% HCl-NE-FE 2990'-2900'. POOH. Ran GR-CCL log 2990'-2800'. Perf w/ 2 SSF, 2976', 77', 78', 79', 80', 81', 82', 83', 84', 85', 2986', total 22 holes. WITH w/ pkr to 2963'. Acidize w/ 924 gals 15% HCl-NE-FE. Divert w/ 160 gals 10# brine w/ 175# rock salt in 20#/1000 gals. guar gum. Pmpd 924 gals 15% HCl-NE-FE. Flush w/ 735 gals TFW. POOH w/ pkr & tbg. WITH w/ tbg, BPMA set at 2960', SN at 2930'. WITH w/ rods & pmp. Pmpd 180, 520 BW, 6 MCF on 11/18/80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. E. Bingham TITLE Senior Analyst DATE November 19, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 3 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO