Porm 9-831a (Feb., 1920) DEPARTMENT	OF THE IN		Let is Cruces O32581-E
	ICAL SURVEI		Lease of Permit
SUNDRY NOTICE	S AND R	EPORTS OF	N WELLS
NOTICE OF INTENTION TO DRILL	X SUBSEC	UENT RECORD OF SHOOT	ING
NOTICE OF INTENTION TO CHANGE PLANS	1 1	D OF PERFORATING CASIN	
NOTICE OF DATE FOR TEST OF WATER SHUT-OFF	NOTICE	OF INTENTION TO PULL	OR OTHERWISE ALTER CASING
REPORT ON RESULT OF TEST OF WATER SHUT-OFF	NOTICE	OF INTENTION TO ABAND	ON WELL
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEC	UENT REPORT OF ABANDO	DNMENT
NOTICE OF INTENTION TO SHOOT	SUPPLE	MENTARY WELL HISTORY	
110 (Section 2017)			
(INDICATE ABOVE BY CHECK	K MARK NATURE OF R	EPORT, NOTICE, OR OTHER	E DATA)
M.F.Sholes B-13 # 4		Hobbs N	.M. 1-26 10 35
			, 19
Following is a notice of intention to	o do work] on l	and under lease	described as follows:
New Merico	Lea		Jal
(State or Territory)	(County or Subdi	vision)	(Field)
	• 112 ·	25s 56 <u>r</u>	N.M.P.M.
Vell No. 4 NW 1/4 Sec			
(14 Sec. and Sec. The well is located 2310 ft. $\begin{bmatrix} 10 \\ S \end{bmatrix}$ of $\begin{bmatrix} 1 \\ S \end{bmatrix}$	No.)	(Twp.) (Ramp 0 ft. [E] of W) (Meridian) line of sec. <u>13</u>
	No.)	(Twp.) (Ramp 0 ft. [E] of W) (Meridian) line of sec. <u>13</u>
(4 Sec. and Sec. The well is located 2310 ft. $\begin{bmatrix} 10 \\ S \end{bmatrix}$ of N The elevation of the derrick floor above sea	No.)	(Twp.) (Ramp (Twp.) (Ramp fit. [E] of W furnish lat) (Meridian) line of sec. <u>13</u>
(14 Sec. and Sec. The well is located 2310 ft. $\begin{bmatrix} \mathbf{N} \\ \mathbf{S} \end{bmatrix}$ of N The elevation of the derrick floor above sea DETAIN itate names of and expected depths to objective sands; show si	line and 2310 a level is Will LS OF PLAN	(Twp.) (Ramp . ft. E) of W furnish lat OF WORK the of proposed casings; indi) (Meridian) line of sec. <u>13</u> er.
(4 Sec. and Sec. The well is located 2310 ft. $\begin{bmatrix} 1 \\ S \end{bmatrix}$ of N The elevation of the derrick floor above sea DETAIN tate names of and expected depths to objective sands; show si	No.) line and 2310 a level is Will LS OF PLAN izes, weights, and lengt other important propose well for or s oil or ga vill be cen .1 water st	(Twp.) (Ramp C. ft. E. of W furnish lat OF WORK the of proposed casings; indi- d work.) oil or gas t as is encoun aented or mu- hut off to p	(Meridian) line of sec. <u>13</u> er a icate mudding jobs, commuting points, and 0 & depth of tored at a lesser dded by approved revent infiltration
(4 Sec. and Sec. he well is located 2310 ft. S of M he elevation of the detrick floor above sea DETAIL ate names of and expected depths to objective sands; show si all o It is proposed to drill a approximately 3350' unless depth. All Casing points w methods of U.S.G.S. and al of other stratas, the foll 13" O.D. casing will be 9-5/8" O.D. casing set of cement or on top of 7" O.D. casing will be	Ine and 2310 A level is Will LS OF PLAN US OF PLAN Well for a oil or ga will be cen l water st lowing cast at about 1 Main Salt set at about 1	(Twp.) (Ramp C. ft. E. of W furnish lat OF WORK the of proposed casings: indi- d work.) OI OF EAS t as is encoun- aented or mu- tut off to p- ing will be 50' cemented .600' cement Beds. Dut 3275' of	(Meridian) line of sec. 13 er. er. icate mudding jobs, communing points, and 0 & depth of tored at a lesser dded by approved revent infiltration run in this well. with 100 Sacks. ed with 600 sacks r on top of oil pay
(4 Sec. and Sec. he well is located 2310 ft. S of N he elevation of the derrick floor above sea DETAIN inte names of and expected depths to objective sands; show ai all of It is proposed to drill a approximately 3350' unless depth. All Casing points w methods of U.S.G.S. and al of other stratas, the foll 13" O.D. casing will be 9-5/8" O.D. casing set of cement or on top of 7" O.D. casing will be and cemented with 400 s made in order to set pi reasonable gas-oil rati	Ine and 2310 A level is Will LS OF PLAN US OF PLAN Well for of soil or ge will be cen l water st lowing cas: at about 1 Main Salt sats of ce acks of ce	(Twp.) (Ramp O ft. E of W furnish lat OF WORK the of proposed casings; indi- d work.) OI OF WORK the of proposed casings; indi- d oF WORK the of proposed casings; indi- d work.) OI OF WORK the of proposed casings; indi- d work.) OI OF WORK the of proposed casings; indi- d oF WORK the of f to p ling will be SO' Cemented .600' cemented .600' cement Bedgs. Out 3275' OF Ement. Drill Dugh to comp	(Meridian) line of sec. 13 er. er. icate mudding jobs, consenting points, and 0 & depth of tored at a lessor dded by approved revent infiltration run in this well. With 100 Sacks. ed with 600 sacks r on top of oil pay a team Sest will be lete well with
(4 Sec. and Sec. he well is located 2310 ft. S of M be elevation of the derrick floor above sea DETAIN tate names of and expected depths to objective sands; show ai all of It is proposed to drill a approximately 3350' unless depth. All Casing points w methods of U.S.G.S. and al of other stratas, the foll 13" O.D. casing will be 9-5/8" O.D. casing set of cement or on top of 7" O.D. casing will be and cemented with 400 s made in order to set pi	line and 2310 a level is Will LS OF PLAN US OF PLAN well for of soil or ga vill be cen l water st lowing cas: at about 1 Main Salt set at about 1 Main Salt set at about 2 her low end o.	(Twp.) (Ramp O ft. E of W furnish lat OF WORK the of proposed casings; indi- d work.) OF WORK Solution of proposed casings; indi- d work.) OF WORK Solution of the proposed casings; indi- d work.) Solution of the proposed casings; indi- d work.) Solution of the proposed casings; indi- d of the proposed c	(Meridian) line of sec. 13 er. er. icate mudding jobs, consenting points, and 0 & depth of tored at a lessor dded by approved revent infiltration run in this well. With 100 Sacks. ed with 600 sacks r on top of oil pay a team Sest will be lete well with
(4 Sec. and Sec. he well is located 2310 ft. S of N he elevation of the derrick floor above sea DETAIN tate names of and expected depths to objective sands; show all approximately 3350' unless depth. All Casing points w me thods of U.S.G.S. and al of other stratas, the foll 13" O.D. casing will be 9-5/8" O.D. casing set of cement or on top of 7" O.D. casing will be and cemented with 400 s made in order to set pi reasonable gas-oil rati See attached a pproved January 29, 1935	Ine and 2310 A level is Will LS OF PLAN US OF PLAN Well for well for a oil or ge will be cen l water st lowing cast at about 1 Main Salt set at about 1 Main Salt set at about 2 A main Salt Satat about 2 A main Salt Satat about 2 A main Salt Satat about 2 A main Salt	(Twp.) (Ramp O ft. E of W furnish lat OF WORK the of proposed casings; indi- d work.) OF WORK Solution of proposed casings; indi- d work.) OF WORK Solution of the proposed casings; indi- d work.) Solution of the proposed casings; indi- d work.) Solution of the proposed casings; indi- d of the proposed c	(Meridian) line of sec. 13 er. er. icate mudding jobs, consenting points, and 0 & depth of tered at a lessor dded by approved revent infiltration run in this well. with 100 Sacks. ed with 600 sacks r on top of oil pay steam best will be lete well with proval.
(4 Sec. and Sec. he well is located 2310 ft. S of M be elevation of the detrick floor above sea DETAIL ate names of and expected depths to objective sands; show si all o It is proposed to drill a approximately 3350' unless depth. All Casing points w me thods of U.S.G.S. and al of other stratas, the foll 13" O.D. casing will be 9-5/8" O.D. casing set of cement or on top of 7" O.D. casing will be and cemented with 400 s made in order to set pi reasonable gas-oil rati See attached a pproved January 29, 1935 (Date)	Ine and 2310 A level is Will LS OF PLAN US OF PLAN Well for of soil or ge will be cen l water st lowing cas: at about 1 Main Salt set at about 1 Main Salt set at about 2 Constructions	(Twp.) (Ramp O ft. E of W furnish lat OF WORK the of proposed casings: indi- d work.) OF a proposed casing ca	(Meridien) line of sec. 13 er. er. icate mudding jobs, communing points, and 0 & depth of tered at a lessor dded by approved revent infiltration run in this well. with 100 Sacks. ed with 600 sacks r on top of oil pay stem best will be lete well with proval.
(4 Sec. and Sec. the well is located 2310 ft. S of M the elevation of the derrick floor above sea DETAIL ate names of and expected depths to objective sands; show ai all of It is proposed to drill a approximately 3350' unless depth. All Casing points w me thods of U.S.G.S. and al of other stratas, the foll 13" O.D. casing will be 9-5/8" O.D. casing set of cement or on top of 7" O.D. casing will be and cemented with 400 s made in order to set pi reasonable gas-oil rati See attached; s pproved January 29, 1935 (Date) Title Thomas G. Taylor, Engine	Ine and 2310 A level is Will LS OF PLAN US OF PLAN Well for of soil or ga will be cen l water sh lowing cas: at about 1 Main Sait set at about 1 Main Sait set at about 1 Main Sait set at about 2 Main Sait	(Twp.) (Ramp O ft. E of W furnish lat OF WORK the of proposed casings: indi- d work.) OF WORK is of proposed casings: indi- d work.) OF WORK is of proposed casings: indi- d work.) OI OF GAS t as is encoun- aented or mu- tut off to p- ing will be SO' cemented. SO' cemented. SO' cemented. SO' cemented. Beds. Out 3275' of ement. Drill bugh to comp- aditions of ap- ompany Conti- By	(Meridian) line of sec. 13 er. er. icate mudding jobs, consuming points, and 0 & depth of tered at a lesser dded by approved revent infiltration run in this well. With 100 Sacks. ed with 600 sacks r on top of oil pay a team sest will be lete well with proval. A contal Oil Co.

۹. .