

COPY TO J.C.C.  
HOBBS (SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.  
Approval expires 12-31-60.

Land Office N.M.


Lease No. 03429

Unit A

RECEIVED

APR 13 1959

U. S. GEOLOGICAL SURVEY  
EL PASO, NEW MEXICO



# SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 11th

1959

Federal  
Well No. 1

is located 660 ft. from N line and 660 ft. from E line of sec. 19

NE 1/4 NE 1/4 - 19  
(1/4 Sec. and Sec. No.)

25 S  
(Twp.)

36 E  
(Range)

NM  
(Meridian)

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

In accordance with telephone conversation between Grady Wright and Mr. Kleeman on April 10th., 1959, application is made to drill well with Cable Tools, as follows:  
Drill 12" hole to approximately 550'. Provided water is encountered, run 10 3/4" casing and cement with 2-5 sacks cement by dumping with beiler. Test for water shut-off. Continue drilling 10 hole thru Rusler lime to anhydrite formation near top of salt. If water is encountered in Rusler lime, run 8 5/8" casing and cement with sufficient cement to assure water shut-off and continue drilling 8" hole to 4000' of oil or gas formation at a lesser depth. Provided oil or gas formation is found, we will discuss with you the pulling of the 10" or 8" casing and cementing of the string left in hole and also the size of oil string to be run and the cementing of same.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Edward C. Donohue  
Sun-Tex Pet. Co.  
Address El Paso, Texas

By Grady Wright  
Title Agent



INSTRUCTIONS FOR COMPLETION:

1. Operator shall furnish and certify to the information called for in Section A.
2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plat the location of the well and certify this information in the space provided.
4. All distances shown on the plat must be from the outer boundaries of Section.
5. If additional space is needed for listing owners and their respective interests as required in question 3, Section A, please use space below

\* "Owner" means the person who has the right to drill into and to produce from any pool and to appropriate the production either for himself or for himself and another. (65-3-29 (e) NMSA 1953 Comp.)