

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE
LC - 032581 (a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFLL
8. FARM OR LEASE NAME
Sholes A
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Jalmat Yates Seven Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 24, T-25S, R-36E
12. COUNTY OR PARISH
LEA
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/22/80 MIRLL. POOH w/rods, pump, tbg. R/H w/workstring. POOH w/RBP. WITH w/
CIBP set at 2918'. Spot 2sx sdc on top of CIBP. Tstd CIBP to 500psi. Perf 2878' -
2899' w/2 JSPF, total 18holes. WITH w/pkr at 2803'. Load backside w/1066ls 2% KCl
water. Acidize w/750gals 15% HCl. Pmpd 366ls 10# brine w/125# rock salt in 20#/1000
gals. guar gum system. Acidize w/750gals. 15% HCl-NE. Flush w/466ls TFW. Kill
well w/5066ls TFW. POOH w/pkr and tbg. R/H w/tbg, SN at 2862'. Ran rods
& pump. Place well on test. Pmpd 8180, 96 BW in 24 hrs. 11/1/80.
Verbal approval per George Stewart 10/23/80

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butler TITLE Administrative Supervisor

DATE 11/5/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

NOV 10 1980

U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO