

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☒
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
LC-032581(a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFU
8. FARM OR LEASE NAME
Sholes A
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Jalmat
Yates Seven Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 24, T-25S, R-36E
12. COUNTY OR PARISH
LEA
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. Kill well w/ TFW. Pull rods, pump, retr. bridge plug set at 2940'. Run tbg. w/ cast iron bridge plug set at 2918'. Test plug to 500psi. Spot 1sk. cement on plug. Spot 150gal 15% HCl-NE-FE acid. Pull tbg. Run GR-CCL log 2905'-2700'. Run 4" csg. gun, 2JSPF, perf 2878', 80', 87', 89', 91', 93', 95', 97', & 2899', total 18 holes. Pull gun. Run tbg w/ treating pkv set @ 2830'. Pump 750gals. 15% HCl-NE-FE. Divert w/ 126gals. 10lb. brine w/ 125lbs. rock salt in a 2016/1000gal quar gum system. Pump 750gals 15% HCl-NE-FE. Flush w/ 504gals. TFW. Pull pkv & tbg. Re-run tbg. and set @ 2890' w/ SN @ 2860'. Run rods and pump. Place well on production and test.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butterfield TITLE Administrative Supervisor

DATE 10/23/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

DATE OCT 27 1980

for DISTRICT SUPERVISOR