

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3247 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 15, 1960
OIL WELL: The production during the first 24 hours was 92 barrels of liquid of which 87% was oil; 13% was emulsion; 13% water; and % was sediment. A.P.I. Gravity 28.6
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy.	1090	T. Devonian		T. Ojo Alamo			
T. Salt	1300	T. Silurian		T. Kirtland-Fruitland			
B. Salt	2860	T. Montoya		T. Farmington			
T. Yates	3090	T. Simpson		T. Pictured Cliffs			
T. 7 Rivers		T. McKee		T. Menefee			
T. Queen		T. Ellenburger		T. Point Lookout			
T. Grayburg		T. Gr. Wash.		T. Mancos			
T. San Andres		T. Granite		T. Dakota			
T. Glorieta		T.		T. Morrison			
T. Drinkard		T.		T. Penn.			
T. Tubbs		T.		T.			
T. Abo		T.		T.			
T. Penn.		T.		T.			
T. Miss.		T.		T.			

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1090	1090	Red Bed				
1090	1300	210	Anhydrite				
1300	2860	1560	Salt & Anhydrite				
2860	3090	230	Dolomite & Anhydrite				
3090	3247	157	Sand, Shale & Dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 19, 1963
(Date)

Company or Operator Standard Production Company
Name H. L. Smith

% OIL REPORTS & GAS SERVICES
Address BOX 763 HOBBS, NEW MEXICO
Position or Title Agent