

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
N. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 032581 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Maralo, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 832, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3021 GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sholes B

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Sholes B
Cooper-Jai11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25, 25S, 36E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plug back & re-perf

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-20-81 - Squeezed perms 2871 to 2910 w/75 sx Class C 3% Halad 4 + 75 sacks Class C 5#/ sack flocele 2% CaCl₂. Squeezed @ 2000#'s. Pressured tubing to 1000 psi and casing to 500 psi - held ok. WOC 12 hours.


10-21-81 - Tagged top cement @ 2832' (New PBTD). Spotted 150 gals 15% HCl from 2822-2734'.

Perf'd Upper Yates gas sands w/4" cased gun w/1 JSPF @:2733; 2734;2735;2736;2742;2746;2747; 2748;2754;2755;2772;2773;2778;2779;2780;2785;2786;2791;2811;2812;2813;2814;2817;2818;2819; 2820;2821;2822;2823;& 2824': (30 holes). Set packer @ 2673'. Pressured annulus to 500 psi - held ok. Acidized w/1800 gals of 15% acid. Dropped 4 ball sealers after each 250 gals acid.

10-23-81 - Sand frac'd Upper Yates perms 2733-2824' (30 holes) w/20,000 gal gelled fresh water & 200 sx 20-40 mesh sand & 100 sx 10-20 mesh sand in two stages.

10-31-81 - Ran 2" x 1 1/2" x 12' pump on 110 - 3/4" rods.

11-9-81 - Put well on production.

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Brenda Coffman

TITLE

Production Clerk

DATE

11-11-81

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NOV 20 1981

U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO

*See Instructions on Reverse Side