

N

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Ralph Lowe **Midland, Texas**
Company or Operator Address
Sholes Well No. **2** in **SE** of **SW** Sec. **25**, T. **25**
Lease
R. **36**, N. **M.P.M.**, **Jal** Field, **east** **1 ea** County.
Well is **660** feet **xxx** of the **North** line and **660** feet **xxx** of the **East** line of **25-25-36**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is **Ralph Lowe** Address **Midland, Texas**
The Lessee is Address
Drilling commenced **May 25,** 19 **47** Drilling was completed **June 25,** 19 **47**
Name of drilling contractor **Self** Address
Elevation above sea level at top of casing **3021** feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from **2945** to **2950** No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10 3/4	36#	8thd		410					
8 5/8	22#	8thd		1225					
7	20#	8thd		2935					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
	10 3/4	410	150	Halliburton		
	8 5/8"	1225		Mudded in		
	7	2935	150	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from **0** feet to **2950** feet, and from feet to feet

PRODUCTION

Put to producing, 19
The production of the first 24 hours was **240** barrels of fluid of which **100** % was oil; %
emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

, Driller, Driller
, Driller, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **30th** **Midland, Texas** **June 30, 1947**
day of **June**, 19 **47** Name **Ralph Lowe**
Notary Public Position **Agent**
Representing **Ralph Lowe**
My Commission expires **June 1, 1949** Address **Midland, Texas**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	10	10	Cellar
10	15	5	Caliche
15	115	100	Sand
115	140	25	Red rock
140	162	22	Sand
162	195	33	Sandy shale
195	235	40	Sand
235	265	30	Sandy shale
265	325	60	Sand
325	340	15	Red rock
340	385	45	Sand and blue shale
385	415	30	Blue shale
415	445	30	Red shale
445	990	545	Red rock
990	1050	60	Anhydrite
1050	1060	10	Water sand
1060	1120	60	Anhydrite
1120	1140	20	Salt
1140	1155	15	Anhydrite
1155	1175	20	Red rock
1175	1240	65	Anhydrite
1240	1250	10	Red rock
1250	1265	15	Salt
1265	1292	27	Anhydrite and red rock
1292	1295	3	Anhydrite
1295	1325	30	Red shale
1325	1348	23	Red rock
1348	1375	27	Anhydrite, salt and potash
1375	1560	85	Salt and potash
1560	1575	15	Salt
1575	1690	115	Salt, anhy, potash
1690	1705	15	Anhydrite
1705	1790	85	Anhydrite, salt and potash
1790	1915	125	Salt and shells
1915	1950	35	Anhydrite
1950	1985	35	Salt
1985	2230	245	Salt, potash & anhydrite
2230	2275	45	Salt
2275	2360	85	Salt and anhydrite
2360	2450	90	Salt and shells
2450	2495	45	Salt and anhydrite
2495	2552	57	Salt
2552	2570	18	Brown lime
2570	2590	20	Lime
2590	2615	25	Brown lime
2615	2950	335	Lime - total depth