

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
CONOCO INC.

3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL + 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) OPEN ADD'L PAY <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE  
LC-032581 (B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
NMFU

8. FARM OR LEASE NAME  
SHOLES B-25

9. WELL NO.  
3

10. FIELD OR WILDCAT NAME  
JALMAT YATES 7 RVRS.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 25, T25S, R36E

12. COUNTY OR PARISH  
LEA

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU 1/27/84. PERF W/2 JSPF @ 2881', 2890', + 2899'. SET RBP @ 2904' + PKR @ 2840'. ACIDIZED W/12 BBLs 15% HCL-NE-FE. FLUSHED W/16 BBLs TFW. REL PKR. REPAIRED SLIGHT CSG LEAK NEAR SURFACE W/25 SXS CMT IN 5 1/2" - 10 3/4" ANNULUS. RESET RBP @ 2918'. RAN PROD EQUIP. Pmpa 130, 932 BW, + 25 MCF 3/14/84.  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butterfield TITLE Administrative Supervisor DATE 5/24/84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY SWC TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL IF ANY  
JUN 2 1984

Carlsbad, NEW MEXICO

\*See Instructions on Reverse Side