



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 030554 (a)
Unit W. T. Joyner

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Robbs, New Mexico - August 22, 1955

Well No. 2 is located 1980 ft. from N line and 1980 ft. from E line of sec. 26

N 1/4 Sec. 26 253 36E N. 21. 2. N.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Cooper-Jal Lea County, New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ? ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

To be drilled with rotary tools from surface to total depth of approximately 5000' in the greens sand. Casing program to be as follows:

SIZE HOLE	SIZE CASING	APPROX. CASING POINT	SACKS CEMENT
11"	8-5/8" OD	1250'	500
7-7/8"	5-1/2" OD	5000'	200

The Halliburton process will be used in cementing both strings of casing and cement will be circulated to surface on the 8-5/8" surface casing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Kelly Oil Company

Address P.O. Box 38

Robbs, New Mexico

By [Signature]

Title Dist. Supt.