



DUPLICATE

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

|   |   |                                     |
|---|---|-------------------------------------|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL |                                     |
| NOTICE OF INTENTION TO CHANGE PLANS         | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING |                                     |
| NOTICE OF INTENTION TO REPAIR WELL          |   |                                     |
| NOTICE OF INTENTION TO DEEPEN WELL          | NOTICE OF INTENTION TO PLUG WELL                      | <input checked="" type="checkbox"/> |

Hobbs, N. M.

Place

June 20, 1945

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Skelly Oil Company Mexico "A" Well No. 1 in CNW SE  
Company or Operator Lease

of Sec. 36, T. 25, R. 36, N. M. P. M., Cooper-Jal Field,  
Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Drilled to TD 3301' - Hole full sulphur water -- no oil. Will run total of 65 sacks cement plugging back to approximately 3125', then let cement set and run collar buster and salvage approximately 2800' of 7" OD Casing. Then fill hole with mud laden fluid and drive lead wool plug at approximately 2800', and plug back to 800' w/ mud laden fluid, then run cement cap and run collar buster and salvage 8-5/8" casing. Will then plug back to surface w/ mud laden fluid and run cement plug and cap and install marker in accordance with the rules and regulations of the Oil Conservation Commission.

Approved JUN 23 1945, 19  
except as follows:

SKELLY OIL COMPANY

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to

Name

Skelly Oil Company

Address

Drawer "D", Hobbs, N. M.

OIL CONSERVATION COMMISSION,

By

Title

Roy Yarbrough  
Plugging