NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTIGES

the Commission.	e of not	tice by checking below:		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	XX	NOTICE OF INTENTION CHEMICALLY TRE	N TO SHOOT OR AT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION OTHERWISE ALTE	TO PULL OR R CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION	TO PLUG WELL	_
NOTICE OF INTENTION TO DEEPEN WELL				
	Hol	bos, Mew Mexico	October 22.	1950
		Place	Date	4//
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen: Following is a notice of intention to do certain wor	rk os da	sarihad halam at the		
Skerry Off Combana	lexico		ell No. 2 in	CNE/4 SE
Company or Operator Le	ase			
f Sec. 36 , T. 25S , R. 36E	, N	. M. P. M., Cooper-Ja	al	Field.
Lea County.				
FULL DETAILS OF	DDAD			
- 0-13 111110 01	LUOL	OSED PLAN OF WOR	K	
FOLLOW INSTRUCTIONS IN THE RU Drilled to total depth of 1325 in sand cemented with 500 sacks cement.	JLES A	ND REGULATIONS OF T	THE COMMISSION Do casing set a	- " - 2
	JLES A alt. F Hallib ours a	ND REGULATIONS OF T lan string of d=5/8"(Durton process used a	THE COMMISSION Do casing set a	- " - 1 - 1 - 1
FOLLOW INSTRUCTIONS IN THE RUDrilled to total depth of 1325' in sand cemented with 500 sacks cement. It to surface. Will let cement set 36 h 10:30 A.M. will drill plug and test of the surface.	JLES A alt. F Hallib ours a	ND REGULATIONS OF T lan string of d-5/8"(purton process used a and on October 23, 19 shutoff.	THE COMMISSION Do casing set a and cement circles 550, at approximately	- " - 1 - 1 - 1
Drilled to total depth of 1325' in sand cemented with 500 sacks cement. to surface. Will let cement set 36 h 10:30 A.M. will drill plug and test of the surface.	JLES A alt. F Hallib ours a	ND REGULATIONS OF Tan string of d-5/8"(Durton process used and on October 23, 19; shutoff.	THE COMMISSION Do casing set a and cement circles 550, at approximately	- " - 1 - 1 - 1
Drilled to total depth of 1325' in sand cemented with 500 sacks cement. to surface. Will let cement set 36 h 10:30 A.M. will drill plug and test of the surface.	JLES A alt. F Hallib ours a	ND REGULATIONS OF Tan string of d-5/8"(Durton process used and on October 23, 19; shutoff.	THE COMMISSION Decasing set a and cement circles 50, at approximately any	- " - 1 - 1 - 1
Drilled to total depth of 1325' in sand cemented with 500 sacks cement. to surface. Will let cement set 36 h 10:30 A.M. will drill plug and test of the surface.	JLES A alt. F Hallib ours a	Skelly Oil Company By	any or Operator	ilated mately
Pollow instructions in the Ru Drilled to total depth of 1325' in s and cemented with 500 sacks cement. to surface. Will let cement set 36 h 10:30 A.M. will drill plug and test of proved follows:	JLES A alt. F Hallib ours a	Skelly Oil Company By Send communications Position Dist. Super Send communications Scally Oil Company	any or Operator intendent ons regarding well t	ilated mately
Drilled to total depth of 1325' in sand cemented with 500 sacks cement. It to surface. Will let cement set 36 h 10:30 A.M. Will drill plug and test of the surface.	JLES A alt. F Hallib ours a	Skelly Oil Company By	any or Operator intendent ons regarding well t	ilated mately
Drilled to total depth of 1325' in s and cemented with 500 sacks cement. to surface. Will let cement set 36 h 10:30 A.M. will drill plug and test of the surface and test of t	JLES A alt. F Hallib ours a	Skelly Oil Company By Send communications Position Dist. Super Send communications Scally Oil Company	any or Operator intendent ons regarding well t	ilated mately