

DUPLICATE

FORM C-105

N

AREA 640 ACRES
LOCATE WELL CORRECTLY

John M. Kelly

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

#208

11158

Mall to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

B ox 5671, Roswell, New Mexico

Jack B Company or Operator
Well No. 2 in SENW of Sec. 19, T. 24-S
Lease 37-E Langlie Mattix Field, Lea County.
N. M. P. M. 2310
Well is 2310 feet south of the North line and 990 feet west of the East line of NW 1/4 of Sec. 19
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is E. E. Jack Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced April 20 19 50 Drilling was completed May 10 19 50
Name of drilling contractor Oil Well Remedial Service Address Odessa, Texas
Elevation above sea level at top of casing 3298 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3002 to 3169 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10 3/4	32	8	seamless	310	Texas				
7	23	8	"	2956	Halliburton				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
12 3/4	10 3/4	310	75	Halliburton		
8 3/4	7	2956	300	Halliburton 2-stage		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3169 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing May 10 19 50
The production of the first 24 hours was 41 B0 in 9 hrs. 100 % was oil; %
emulsion; % water; and % sediment. Gravity, Be. 37
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in. 1250#

EMPLOYEES

W. Britt Driller
S. Land Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this Roswell, New Mexico May 20, 1950
day of May 19 50
Notary Public
Name John M. Kelly
Position Owner
Representing John M. Kelly
Address Box 5671, Roswell, N.M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	1150	1150	Caliche and Red Beds
1150	1440		Anhydrite
1440	2840		Salt
2840	3002		Brown Lime
3002	3169		Yates sand and sandy lime