

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 7, 1948

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation A.G. Falby Well No. 1 in the _____
Company or Operator Lease
NW 1/4 SW 1/4 of Sec. 19, T. 24S, R. 37E, N. M. P. M.,
Langlie-Mattix (Ext.) Field, Lea County.

The dates of this work were as follows: December 6, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on December 4, 19 48
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3824' Total Depth, 3624' Plugged Back Depth. 5 1/2" Casing set at 3350' Ran Temperature Survey found top of cement at 2126'. 43.8% of calculated fill. Nippled up Picked up tubing, found top of cement at 3270' Tested casing with 1000# for 30 minutes, drilled out cement to 3318' tested casing with 1000# for 30 minutes was O.K. Gun perforated from 3100' to 3190', 4 shots per foot, total of 360 holes, 106 jts. of 2-3/8" OD 4.7# EUE, J-55, Tubing & KV-30 Guiberson Packer, Tubing set at 3190'

Witnessed by L.W. Gordon Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this _____

7th day of December 1948

Will Hale Taylor
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name L.W. ToppPosition Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

Roy Yankovich
Name
Title