

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting 5½" Casing	X

December 5, 1948

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation A.G. Falby Well No. 1 in the _____
Company or Operator Lease

NW ¼ SW ¼ of Sec. 19, T. 24S, R. 37E, N. M. P. M.,
Langlie-Mattix (Ext.) Field, Lea County.

The dates of this work were as follows: December 5, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on December 4, 1948
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3824' Total Depth, Line. Went in hole with open end drill pipe. Mixed 50 sacks Lone Star Reg. cement. Flushed with 51 bbls. mud, pulled up to 3695' and reversed out Approx. 6 sacks cement. Layed down 4½" drill pipe, Ran 83 joints 5½" O.D. 15.5#, J-55, R-3, 8Rd. Thd. S.S. Casing (New). Casing set at 3350'. Cemented with 150 sacks Lone Star Common, 250 sacks El Toro Common and 50 sacks Incor cement, plug stopped at 3270' with 1000# pump pressure at 2:45 A.M. 12-5-48. Spot welded first 6 collars, Weatherford Scratcher's set at 3100'-3116'-3122'-3138'-3144'-3150'-3160'-3170'-3190'-3200'-3347' Total of 12. Baker Centralizers at 3110'-3180'-3250'-3310' (Total of 4)

Witnessed by D.N. Gordon Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this _____
5th day of December 1948

Will Hale Taylor
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Ray Taylor
Position Asst. Dist. Supt.
Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

Ray Taylor
Name
Title