

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

October 13, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation A. G. Falby Well No. 3 in the

NE 1/4 SW 1/4 of Sec. 19, T. 24-S, R. 37-E, N. M. P. M.,
Langlie-Mattix Field, Lea County.

The dates of this work were as follows: October 12, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on October 10, 1949
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3680' - Total Depth - Lime. 3241' P.B.D. Connected 5-1/2" casing, ran 4-3/4" bit & 2-3/8" OD NBE tubing and tested 5-1/2" casing with 1000# for 1/2 hour - there was no pressure drop. Drilled 60' of wash cement from 3181' to 3241', circulated hole clean and pressured up on 5-1/2" casing with 1000# for 1/2 hour - there was no pressure drop. Temperature Survey - top of cement on outside of 5-1/2" casing at 225', actual fill 3095', ratio of actual to calculated fill 37.2%.

Witnessed by <u>D. W. Gorden</u>	<u>Amerada Petroleum Corporation</u>	<u>Farm Boss</u>
	Name	Company
Subscribed and sworn before me this _____	I hereby swear or affirm that the information given above is true and correct.	
_____ day of _____ 19 _____	Name <u>H. W. Topp</u>	
	Position <u>Assistant District Superintendent</u>	
Notary Public	Representing <u>Amerada Petroleum Corporation</u>	
	Company or Operator	
My commission expires _____	Address <u>Drawer D, Monument, New Mexico</u>	

Remarks:

Name

Title