


AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

John M. Kelly Box 5671, Roswell, New Mexico
Company or Operator Address
Jack B Well No. **1** in **SWNW** of Sec. **19**, T. **24-S**
Lease
R. **37-E**, N. M. P. M., **Langlie Mattix** Field, **Isa** County.
Well is **2310** feet south of the North line and **4950** feet west of the East line of **Section 19**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is **E. E. Jack** Address
The Lessee is Address
Drilling commenced **March 25** 19 **50** Drilling was completed **April 15** 19 **50**
Name of drilling contractor **Oil Well Remedial Service** Address **Odessa, Texas**
Elevation above sea level at top of casing **3298** feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from **3004** to **3167** No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
9 5/8	32	8	beam-	267	Texas				
7	20	8	less	2975	Halliburton				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
10 3/4	9 5/8	267	75	Halliburton		
8 3/4	7	2975	400	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing April 15 19 50
The production of the first 24 hours was 56 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be. 37
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in

EMPLOYEES

Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this Roswell, New Mexico April 25, 1950
day of April 19 50
Notary Public
My Commission expires
Name John M. Kelly
Position Owner
Representing John M. Kelly Operator
Address Box 5671, Roswell, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	1150	1150	Caliche Red Beds
1150	1420	270	Anhydrite
1420	2820	1400	Salt
2820	2995	175	Brown Lime
2995	3167	172	Yates Sand & Sandy Lime