

N / MEXICO OIL CONSERVATION COMMISSION  
~~Santa Fe, New Mexico~~ Hobbs, N. M.

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		<del>Report Cementing first string of casing</del>	

Hobbs, N. M.

Feb, 14, 1937

Place

Date

~~OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.~~ Hobbs, N. M.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Shell Petroleum Corp.

J. F. Black

Well No. 1

in the

SE 1/4

Company or Operator

of Sec. 21

Lease

T. 24-S

R. 37 E

N. M. P. M.,

Mattix

Field,

Lea

County.

The dates of this work were as follows: Casing Cemented on 2-12-37

Notice of intention to do the work was [was not] submitted on Form C-102 on 2-12-37  
 and approval of the proposed plan was [was not] obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The first string of casing to be cemented in this well is 8 5/8" O.D. 32# S.S. S.H. casing. It was landed at 1450 in the basal Rustler section immediately above the Castile salt. An outside string of 10 1/2" casing was pulled. To protect fresh water sands the 8 5/8" casing was cemented with 300 sacks in an endeavour to circulate. Circulation was not obtained but the cement was definitely located 50 feet from the surface. 28 sacks of cement were pumped down the outside of the casing bringing the cement to the surface.

Witnessed by

Name

Company

Title

Subscribed and sworn to before me this

day of

March, 1937

*Patricia J. [unclear]*  
 Notary Public

My Commission expires

1-27-37

I hereby swear or affirm that the information given above is true and correct.

Name

E. H. Kimmey

Position

District Foreman

Representing Shell Petroleum Corp.

Company or Operator

Address Dr. 1457 Hobbs, N. M.

Remarks:

Name

Title