

APPROVED

Form 9-881a
(Feb. 1961)

AUG 16 1963

COPY 1 O. C. C.

Budget Bureau No. 42-R358.4.

Form Approved.

Date 8-16-63

J. L. GORDON
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

103BBS

Land Office

0321004

Lease No.

Unit

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

M 3150

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of Dual Completion.....	x

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

South Mattix Unit

August 12,

63

19

Well No. 3 is located 660 ft. from N line and 1980 ft. from E line of sec. 22
NW/4, NE/4, Sec. 22 T-24-S, R-37-E NMPM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Fowler-Tubb Loa New Mexico
 (County or Subdivision) (State or Territory)
Fowler-Blinnery

The elevation of the derrick floor above sea level is 3264 ft. RDB

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
 in points, and all other important proposed work.)
 TD 10,507', PBD 6246'. In accordance with Form 9-551d approved 5-29-63, the Silurian
 Pool was abandoned by setting a retainer set at 6350' and squeezing perforations
 7180'-7455' with 300 sx. cement. Left 104' of cement on top of retainer.
 TUBB ZONE - was perforated at intervals 5930'-33, 5939'-44', 5946'-51', 5970'-75'
 6068'-72', 6082-37' with 2 SPF. Acidized with 6000 gallons of acid and fraced with
 30,000 gallons oil and 30,000# sand with 2,000# glass beads. Set Baker Model "D"
 packer at 5800'. On PT well flowed 60 BLO x 582 MCF gas 24 hrs. 12/64" ch. TPF 1600,
 CPF 1900, 500 BLO to Rec. Shut-In.
 BLINNERY ZONE - was perforated at intervals 5372'-83', 5395-5403', 5452'-57', 5475'-81',
 5532'-42', 5600'-03', 5610'-16' 5627'-30' with 2 SPF. Acidized with 2900 gallons. On
 PT flowed 126 BO x 0 BW 24 hrs. on 18/64" choke. TPF 1280, CPC 1725, GOR 2220.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum CorporationAddress Post Office Box 66Hobbs, New Mexico

By

Title Area Superintendent